



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
© COPYRIGHT - By - ALL RIGHTS RESERVED.

SUGGESTED MATING TAB

SHOULDER MAY BE ELIMINATED IF NOT FEASIBLE

1 MATL: 1/2 H BRASS OR NICKEL PL STEEL.  
 2 NO BURRS PERMISSIBLE AT HOLE.  
 3 MUST BE FLAT WITHIN 0.076 [.003] OVER THIS LENGTH.  
 4 TIN PLATING IS REQUIRED ON BRASS WHEN TERMINAL TEMP. IS OVER 225°F  
 5 HOLE MUST BE SYMMETRICAL ABOUT TAB C WITHIN 0.076 [.003]

\* TO BE USED ONLY WHEN SHOULDER IS ELIMINATED.

SECTION B-B

SECTION C-C

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AF	50	P4	REVISED PER ECR-12-013486	06JAN13	KH KR

1 DIMENSIONS IN BRACKETS ARE IN INCHES.  
 2 CONTINUOUS STRIP ON REELS.  
 3 THE 1.40 [.055] / 1.27 [.050] DIMENSION MUST BE MAINTAINED BY THE APPLICATOR CUT-OFF TO ENSURE THE PROPER LOCKING FUNCTION OF THE RECEPTACLE.  
 4 WIRE SIZE IS 0.3-0.8mm [22-18] AWG  
 5 INSULATION RANGE IS 1.52-2.54 [.060-.100] DIA  
 6 GOLD PLATE 0.00127 [.000050] MIN THK OVER 0.00127 [.000050] MIN NICKEL PLATE  
 7 PREPRODUCTION - FASR REQ  
 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

VIEW A-A

6	PRE-TIN PLATED	63119-4
7	UNPLATED	63119-3
	TIN PLATE	63119-2
	FINISH	63119-1
		PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	7/28/86	TE Connectivity	
DIMENSIONS: mm [INCHES]		CHK	JR RUTH	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	G YETTER	RECPT, POSITIVE LOCK, .250 SERIES	
0 PLC	± -	PRODUCT SPEC	R KUZO	SIZE	CAGE CODE
1 PLC	± -	APPLICATION SPEC	114-2074	A2	00779
2 PLC	± -	WEIGHT	-	DRAWING NO	C=63119
3 PLC	± 0.25 .010	CUSTOMER DRAWING		SCALE	4:1
4 PLC	± -	FINISH	SEE TABLE	SHEET	1 OF 1
ANGLES	± -			REV	P4

1471-9 (3/11)