



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





WORLD BAND GSM/GPS ANTENNA IDEAL WHEN RECEPTION IS A MUST

The World antenna is a high-performance, low-profile cellular and GPS antenna. The antenna supports AMPS, GSM, PCS and DCS bands and is ground plane independent. The antenna is suited for applications inside of a vehicle or can be used externally. It is weather resistant with an IP-67 Ingress Protection rating.

Laird Technologies is a leading supplier of mobile antenna solutions for automotive, asset tracking and consumer electronics industries. Products include cellular antennas (AMPS, GSM/DCS/PCS, UMTS), GPS antennas, entertainment antennas (AM/FM, DAB, DVB-T, satellite radio, TV), mobile communication antennas (Bluetooth®, DSRC, RKE, TPMS, WLAN), satellite communication antennas and battery packs.

Leveraging our experience in M2M wireless modules, Laird Technologies also designs smart antennas integrating functionalities such as cellular, WLAN and Bluetooth modems, GPS receivers and vehicle networking. All of these capabilities can be further integrated into M2M devices that add control electronics and firmware, providing the latest evolution in telematics systems.

FEATURES

- The cost-effective solution transmits voice and data while measuring only 105 x 65 x 25 mm
- Sleek, durable housing mounts on either a ground plane or no ground plane surface
- Compact, high-performing design allows for hidden in-cab installations
- Vastly outperforms competitive solutions in the market
- Multiple mounting solutions
- Weather resistant, IP-67 rating

APPLICATIONS

- General automotive aftermarket
- Fleet logistics, tracking, and diagnostics
- Theft protection
- Vehicle and asset recovery
- Navigation systems
- Infotainment systems
- On-board computing

BENEFITS

- Low total-cost implementation
- High-performance RF reception
- Easy installation
- Small package size
- Meets enhanced environmental specifications
- Ground plane independent

global solutions: local support™

Americas: +810.695.9810
Europe: +44.1628.858.940
Asia: +852.2268.6567



Innovative **Technology**
for a **Connected** World

Asset Tracking External Antenna

Cell+GPS|World

External World

AMPS / GSM DCS / PCS GPS

ANTENNA SPECIFICATION

Frequency Range	824-896 MHz or 880-960 MHz	1710-1880 MHz or 1850-1990 MHz	1575.42 MHz
Peak Gain	0 dBi	2.0 dBi	4.5 dBi @ Boresight
Polarization	Linear	Linear	RHCP
Impedance	50 Ω	50 Ω	50 Ω
Output VSWR (Min. Performance)	≤ 2.5:1	≤ 2.5:1	≤ 2:1

LNA SPECIFICATION

Gain (Max)	—	—	30 dB
Noise Figure	—	—	≤ 2.0 dB
Supply Voltage	—	—	3.0 ± 0.3V
Current (typical)	—	—	20 mA
Input P1dB	—	—	≥ -27 dBm
Output VSWR	—	—	≤ 2:1

MECHANICAL SPECIFICATION

Dimension	105 x 65 x 25 mm
Radome Material	Black ASA + PC (Cycloley)
Connector	SMC for cellular, SMA for GPS
Cable Length	6000 mm
Cable Type	RG-174
Mounting Method	Adhesive, Hook & Loop

ENVIRONMENTAL SPECIFICATION

Operating Temperature	-40°C to +85°C
Humidity	Operation 95% RH at 65°C
Ingress Protection	IP-67
Drop Test / Shock	50 g shocks 10x3 axis / 1 meter drop 6 axis
Vibration	10-1000 Hz vibration 1 hour 3 axis

ORDERING INFORMATION

Part Number	637117
Customization available w/MOQ	Cable type, length, connector type, mounting method

TEL-DS-EXTERNAL WORLD 1210

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.