



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Applicable standard					
Rating	Operating temperature range	-35 °C to +85 °C (Note1)	Storage temperature range	-10 °C to +60 °C (Note3)	
	Operating humidity range	40% to 80% (Note2)	Storage humidity range	40% to 70% (Note3)	
	Voltage	250 V AC	Applicable connector	DF1E-*S-2. 5C	
	Current	AWG20 to 24: 3A AWG26: 2A AWG28: 1A AWG30: 0. 5A	UL, CSA	Voltage	AC 30V
			Current	AWG20 to 22: 3A AWG24 to 28: 1A AWG30: 0. 5A	
Specifications					
Item	Test method		Requirements		QT AT
Construction					
General examination	Visually and by measuring instrument.		According to drawing.		X X
Marking	Confirmed visually.				X X
Electric characteristics					
Contact resistance millivolt level method.	20 mV MAX, 1 mA(DC or 1000 Hz).		30 mΩ MAX.		X —
Insulation resistance	500 V DC.		1000 MΩ MIN.		X —
Voltage proof	650 V AC for 1 min.		No flashover or breakdown.		X —
Mechanical characteristics					
Mechanical operation	30times insertions and extractions.		① Contact resistance: 30 mΩ MAX. ② No damage, crack or looseness of parts.		X —
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 2 h, for 3 directions.		① No electrical discontinuity of 1 μs. ② No damage, crack or looseness of parts.		X —
Shock	490 m/s <sup>2</sup> duration of pulse 11 ms at 3 times for 3 directions.				X —
Environmental characteristics					
Rapid change of temperature	Temperature -55→ 5 to 35→+85→ 5 to 35 °C Time 30→ 5 max→ 30→ 5 max min Under 5 cycles.		① Contact resistance: 30 mΩ MAX. ② Insulation resistance: 1000 MΩ MIN. ③No damage, crack or looseness of parts.		X —
Damp heat (Steady state)	Exposed at 40 ± 2 °C, 90 to 95 %, 96 h.		① Contact resistance: 30 mΩ MAX. ② Insulation resistance: 500 MΩ MIN. ③No damage, crack or looseness of parts.		X —
Resistance to soldering heat	1) Automatic soldering (flow) Solder temperature, 260 °C for Immersion,duration, 10 sec. 2) Manual soldering Soldering iron temperature : 300 °C, Soldering time : 3 sec. No strength on contact.		No deformation of case of excessive looseness of the terminals.		X —
Solderability	Soldered at solder temperature, 235 °C for insertion duration, 5 s.		Solder shall cover a minimum of 95 % of the surface being immersed.		X —
Remarks					
Note1: Include the temperature rising by current.					
Note2:No condensing.					
Note3:Apply to the condition of long term storage for unused products before pcb on board. After pcb board,operating temperature and humidity range is applied for interim storage during transportation.					
Count	Description of revisions		Designed	Checked	Date
△					
			Approved	KI. AKIYAMA	15. 06. 16
			Checked	KI. AKIYAMA	15. 06. 16
			Designed	TS. KUMAZAWA	15. 06. 15
			Drawn	MI. SAKIMURA	15. 06. 15
Unless otherwise specified, refer to IEC 60512.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			Drawing no.		ELC-336779-35-00
HRS	Specification sheet		Part no.	DF1EG-*P-2. 5DSA (35)	
	Hirose electric co., ltd.		Code no.	CL541	△ 1/1

FORM HD0011-2-1

TO