



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Made in the United States of America

### Description:

Dual Layer mat is a .060" thick, 2-layer, dissipative dual layer rubber material. It is designed to provide a path to ground and eliminate static charge generation when used as a worksurface table mat, shelf liner, and cart liner. The surface resistance ( $1 \times 10E6 < 1 \times 10E9$  ohms Rtt) of the color top layer meets the ANSI/ESD S20.20 worksurface required limit and the ANSI/ESD S4.1 recommendation for contact with ESD susceptible items. The conductive ( $< 1 \times 10E6$  ohms Rtt) black bottom layer reduces the resistance to ground (Rtg) from the top of the surface to the groundable point ground and allows the mats to be used with [ESD workstation monitors](#).

### Color Dissipative Top Layer Electrical Properties:

Property	Test Method	Value
Charge Decay:	FTMS 101C, M 4046	<0.01sec.
Rtt Resistance:	ANSI/ESD S4.1	$1 \times 10E6 < 1 \times 10E9$ ohms
Rtg Resistance:	ANSI/ESD S4.1	$1 \times 10E6 < 1 \times 10E9$ ohms

### Disclaimer:

All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized offers of Desco Industries, Inc.

### RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at [Desco.com](#).

### Limited Warranty:

Desco warrants for one year that Dual Layer Rubber matting products will be free of defects in materials and workmanship. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by [Desco Limited Warranty](#).

### Tolerances:

Width  $\pm .250"$   
Length  $\pm .250"$  every 1 linear foot of running material.

### Specifications:

**Thickness:** 0.060"  
**Tolerance:** Thickness  $\pm .005"$   
**Colors\*:** Light Blue, Grey, Dark Blue

\*Color and texture may vary between lots

**Grounding:** This material must be properly grounded for optimum electrical performance. See Tech Bulletin [TB-2000](#) for mat grounding instructions.

**Cleaning:** For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our [Reztore Surface & Mat Cleaner](#). Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

**Use With Continuous Monitor:** This material may be used with [ESD workstation continuous monitors](#).

### Mat Top Kit Item Numbers

Size	Light Blue	Dark Blue	Grey
24" x 36"	<a href="#">66211</a>	<a href="#">66217</a>	<a href="#">66223</a>
24" x 48"	<a href="#">66212</a>	<a href="#">66218</a>	<a href="#">66224</a>
30" x 60"	<a href="#">66213</a>	<a href="#">66219</a>	<a href="#">66225</a>
30" x 72"	<a href="#">66214</a>	<a href="#">66220</a>	<a href="#">66226</a>
36" x 72"	<a href="#">66215</a>	<a href="#">66221</a>	<a href="#">66227</a>

### MAT TOP KIT INCLUDES

1 Benchmat, size as specified  
1 Ground Cord and Push and Clinch Snap

### Roll Material Item Numbers

Size	Light Blue	Dark Blue	Grey
24" x 50'	<a href="#">66200</a>	<a href="#">66204</a>	<a href="#">66208</a>
30" x 50'	<a href="#">66201</a>	<a href="#">66205</a>	<a href="#">66209</a>
36" x 50'	<a href="#">66202</a>	<a href="#">66206</a>	<a href="#">66210</a>

### Tray Liner Item Number

Size	Light Blue	Dark Blue	Grey
16" x 24"	<a href="#">66216</a>	<a href="#">66222</a>	<a href="#">66228</a>

Tray liner has 1" radius corners and does not include grounding hardware.

Specifications and procedures subject to change without notice.

## Dual Layer Rubber Matting

# DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](#)  
PHONE (909) 627-8178  
DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370

**DRAWING NUMBER**  
66200

**DATE:**  
September  
2012