



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PART NUMBER: 688LMU035M2BG

+105°C, LONG LIFE 2000 HRS

PARTS ARE ROHS COMPLIANT

FEATURES

bulk filtering, high current, snap mount leads, 105C

APPLICATIONS

Bulk filtering, switching power supplies

ELECTRICAL SPECIFICATIONS

Capacitance: 6800 uF

Dissipation Factor: 0.25 Max at 120 Hz

Temperature Range: -40°C to +105°C

ESR: 60.95 milliOhms Max at 20°C and 120 Hz

Impedance: N/A

Tolerance: -20 % , +20 %

WVDC: 35 Volts DC

SVDC: 44 Volts DC

Ripple Current: 2.53 A at 120 Hz and 105°C

Impedance Ratios: -25°C/20°C - 3
-40°C/20°C - 6

Leakage Current: .02CV or 2000uA, whichever is less 2000 uA after 5 Minutes

Load Life: 2000 hours at 105°C with 100 % of rated voltage and with 100 % of rated ripple current

Max Capacitance Change: ≤20% of initially measured value

Dissipation Factor Change: ≤200% of maximum specified value

Leakage Current: ≤100% of maximum specified value

Ripple Current Multipliers

Frequency Multipliers:

50 Hz	120 Hz	400 Hz	1 kHz	10 kHz	100 kHz
0.9	1	1	1.15	1.25	1.25

Temperature Multipliers:

45°C	60°C	70°C	85°C	75°C	85°C	105°C	125°C
1	1	1	1	1	1	1	1

PHYSICAL DIMENSIONS

Diameter (D): 22 mm +/- 1 mm

Length (L): 45 mm, +/- 2 mm

Lead Spacing (S): 10 mm, +/- 0.1 mm

Lead Wire Diameter (d): 1.5 mm, +/- 0.5 mm

Lead Length (LL): 6.3 mm, +/- 1 mm

Lead Finish: Matte Tin

Coating: Brown PVC sleeving

