



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Waber-by-Tripp Lite 6-Outlet (77.6mm center-to-center spacing) Industrial Power Strip, 15-ft. Cord

MODEL NUMBER: 6SPDX-15



### Highlights

- 6 outlets
- 15-ft. cord
- 12.5-in. length
- Lighted master switch
- All-metal housing

### Package Includes

- 6SPDX-15 Power Strip
- Warranty information
- Instruction manual

### Description

Tripp Lite's 6SPDX-15 Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 6 NEMA 5-15R output receptacles with 1.505-in. center-to-center spacing, 15-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 6SPDX-15 ideal for distributing alternate waveform UPS or generator power. Features rugged metal housing, lighted power switch with integrated 15A resettable circuit breaker and attractive beige color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 6 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5-15R output receptacles with 1.505-in. center-to-center spacing
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15A power handling capacity
- 15-foot AC line cord

## Specifications

### OVERVIEW

UPC Code

037332108074



| <b>OUTPUT</b>  |  |
|--|--|
| Frequency Compatibility                              | 50 / 60 Hz   |
| Output Receptacles                                   | (6) 5-15R  |
| Circuit Breaker (amps)                               | 15   |
| Outlet Spacing                                       | 1.505 in.  |
| Outlet Orientation                                   | Single row of 6  |
| Right-Angle Outlets                                  | No   |
| <b>INPUT</b>   |  |
| Nominal Input Voltage(s) Supported                   | 120V AC  |
| Recommended Electrical Service                       | 15A 120V   |
| Input Connection Type                                | NEMA 5-15P   |
| Input Cord Length (ft.)                              | 15   |
| Input Cord Length (m)                                | 4.57   |
| Voltage Compatibility (VAC)                          | 120  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>         |  |
| Switches   | Lighted combination switch / circuit breaker                   |
| <b>PHYSICAL</b>                                      |  |
| Shipping Dimensions (hwd / in.)                      | 2.00 x 5.80 x 14.40  |
| Shipping Dimensions (hwd / cm)                       | 5.08 x 14.73 x 36.58   |
| Shipping Weight (lbs.)                               | 3.10   |
| Shipping Weight (kg)                                 | 1.41   |
| Unit Dimensions (hwd / in.)                          | 12.5 x 2.5 x 1.5   |
| Unit Dimensions (hwd / cm)                           | 31.75 x 6.35 x 3.8   |
| Material of Construction                             | Metal  |
| Integrated Keyhole Mounting Tabs                     | Keyhole mounting tabs enable mounting to a variety of surfaces |
| Receptacle Color                                     | Beige  |
| Color (AC Line Cord)                                 | Beige  |
| Outlets Measurement (Center to Center)               | 77.60mm  |
| Keyhole Slot Mounting Measurement (Center to Center) | 203.2mm  |
| <b>CERTIFICATIONS</b>                                |  |
| UL1363 (Power Tap)                                   | UL1363   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                           |
|-------------------------------------|---------------------------|
| cUL / CSA (Canada)                  | cUL                       |
| <b>WARRANTY</b>                     |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>