



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





RF550 Rework Flux

High-Reliability, Zero-Halogen, No-Clean

Product Description

Kester RF550 is a high-reliability, zero-halogen, no-clean rework flux designed for electronic component rework and repair applications. RF550 has a gel-like consistency and is packaged in syringes for easy dispensing. RF550 can be precisely dispensed onto specific areas that require flux. After being dispensed, RF550 stays in place until soldering occurs. RF550 has excellent performance in applications requiring high reliability. RF550 is the ideal choice for QFP or BGA semi-automated rework applications, and is well suited for use with through-hole repair. RF550 compliments Kester's high reliability line of products which are formulated to leave safe residues. RF550 can be used in combinations with Kester no-clean flux-cored solder wires, no-clean solder pastes and no-clean liquid fluxes without any compatibility risks.

Performance Characteristics:

- Zero-halogen (none intentionally added)
- Compatible with most no-clean chemistries
- Formulated to compliment Kester's high-reliability no-clean product line: NP505-HR Solder Paste, NF372-TB Soldering Flux, SELECT-10 Selective Soldering Flux and 296 Flux-Cored Wire
- Classified as ROL0 per J-STD-004B

RoHS Compliance

This product meets the requirements of the Restriction of Hazardous Substances (RoHS) Directive, 2015/863 for the stated banned substances.

Physical Properties

Viscosity (typical): 310 poise
Malcom Viscometer @ 10 rpm and 25°C

Acid Number (typical): 162 mg
KOH/g of flux
Tested to J-STD-004, IPC-TM-650, Method 2.3.13

Reliability Properties

Copper Mirror Corrosion: Low
Tested to J-STD-004B, IPC-TM-650, Method 2.3.32D

Halogen Content: None Detected
Tested to J-STD-004B, IPC-TM-650, Method 2.3.2.81

SIR, IPC: Pass
All Readings $>1.0 \times 10^8 \Omega$
Tested to IPC-TM-650 2.6.3.7
Test Conditions: 40°C, 90% RH, 7 days, 12.5V

Corrosion Test: Low
Tested to J-STD-004B, IPC-TM-650, Method 2.6.15

Electrochemical Migration (ECM):
Pass
Tested to J-STD-004B, IPC-TM-650, Method 2.6.14.1
Test Conditions: 65+/-2°C; 85+3/-0 % RH

 **Cleaning**

RF550 is a no-clean formula. The residues do not need to be removed for typical applications. Although RF550 is designed for no-clean applications, its residues can be easily removed using automated cleaning equipment (in-line or batch) with a variety of readily available cleaning agents. If residue removal is required, call Kester Technical Support.

 **Storage, Handling and Shelf Life**

Shelf life is 1 year from the date of manufacture when stored between 0-10°C (32-50°F).

 **Health and Safety**

This product, during handling or use, may be hazardous to your health or the environment. Read the Safety Data Sheet and warning label before using this product.