

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









**RUGGED 4G LTE GATEWAY FOR UTILITY APPLICATIONS** 



Provides a 4G LTE connection to remote serial or IP-based utility and industrial devices

The Digi Utility Communication Hub gives utilities and energy service providers a secure, reliable 4G LTE connection for Distribution Automation and Metering applications.

Each hub contains a Digi TransPort® WR21, Digi's 3G/4G LTE enterprise router, with two Ethernet ports and a software-selectable RS-485 connection, housed in an IP66 polycarbonate enclosure. Within the enclosure, a battery provides backup power and an DIN rail and auxiliary power support 3rd party devices connected to the WR21.

The Utility Communication Hub is perfect for communicating with C&I meters and meter banks, recloser and switch

controllers, substation equipment, pressure stations, and other utility and industrial infrastructure assets.

Digi TransPort 4G LTE routers can communicate with any meter or controller with an Ethernet or serial port. Known compatibility with GE, Elster, Landis & Gyr, Schneider, Jemstar and Shark meters.

#### **BENEFITS**

- Software-defined multicarrier 4G LTE lets operators software select and change the cellular carrier
- Enterprise routing supports the encryption, logging and security features required for critical infrastructure compliance
- 2 Ethernet ports and software selectable RS-485 support a broad range of remote devices
- Rugged IP66 enclosure protects from the elements
- DIN rail and power support 3rd party equipment like dataloggers and meters
- Battery backup and 277 VAC power input support critical utility applications

### **RELATED PRODUCTS**













# APPLICATION EXAMPLE **Encrypted WAN** UTILITY HEADQUARTERS DIGI REMOTE MANAGERSM METERING OR DISTRIBUTION INFRASTRUCTURE UTILITY COMMUNICATION HUB

SPECIFICATIONS	DIGI UTILITY COMMUNICATIONS HUB	
ENCLOSURE SPECS		
ENCLOSURE	12 x 10 x 6 hinged box assembly; UV-resistant high-impact polycarbonate	
ENVIRONMENTAL RATING	IP66	
OUTSIDE DIMENSIONS (L X W X H)	11.94 in x 9.94 in x 6.23 in (30.33 cm x 25.25 cm x 15.82 cm)	
WEIGHT	15.25 lb (6.90 kg)	
SPECIFICATIONS	DIGI TRANSPORT® WR21	
GENERAL		
TARGET APPLICATION	Commercial and Industrial metering, substation network connectivity or serial telemetry requiring higher security	
MANAGEMENT	HTTP, HTTPS, FTP, SFTP, SSL, SMTP, SNMP (v1/v2c/v3), SSH, Telnet and CLI for web management; Remote management via software tool (option); SMS management, Protocol analyzer, Ability to capture PCAP files for use with Wireshark	
SECURITY	RADIUS, TACACS+, SSL, SSLv2, SSLv3, FIPS 197, L2TP, (5 tunnels included - 50 max on WR41, 200 max on WR44.); IPSec with IKEv1, IKEv2, ISAKMP; DES, 3DES and AES up to 256-bit encryption; Simple Certificate Enrollment Protocol (SCEP) for X.509 certificates, Open VPN and PPTP; IPSec/PPP/L2TP VPN Server support; IP pass-through	
ROUTER/FIREWALL	Bridging, NAT/NAT-Traversal, NAPT forwarding; PPP, PPPoE, GRE; IP Routing Protocols: PPP, GRE, RIP (v1 & v2), OSPF, SRI, BGP; IP Failover: VRRP, VRRP+™; VLAN support; STP (Spanning Tree Protocol); Stateful inspection firewall with scripting; Modbus over UDP/TCP; DHCP; Dynamic DNS client compatible with BIND9/No-IP/DynDNS; Automatic failover/failback to second GSM network/Standby APN, Optional IPv6	
INTERFACES		
SERIAL	1 DB-9F RS-232/422/485	
ETHERNET	2 Ethernet ports	
BATTERY	SLA 1.5 Ah battery included, 20 minute runtime	
POWER INPUT	105-277 VAC	
INTERNAL MOUNTING OPTIONS	DIN rail with supplied power 24 VDC @ 350 mA (max), 6.25 in x 4.50 in (158.75 mm x 114.3 mm)	
ANTENNA TYPES	Cellular	
ENVIRONMENTAL		
OPERATING TEMPERATURE	-20° C to +55° C; -25° C to +70° C with reduced cellular performance Wi-Fi models: -5° C to +55° C; -10° C to +70° C with reduced performance	

PART NUMBERS	DESCRIPTION
70002529	Digi TransPort WR21 - Utility Communication Hub
70002530	Digi TransPort WR21 - Utility Communication Hub (International)

**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

@ 1996-2016 Digi International Inc. All rights reserved. All trademarks are the property of their respective owners.

DIGI INTERNATIONAL WORLDWIDE HQ 877-912-3444 / 952-912-3444 / www.digi.com

**DIGI INTERNATIONAL FRANCE** +33-1-55-61-98-98 / www.digi.fr

**DIGI INTERNATIONAL JAPAN** +81-3-5428-0261 / www.digi-intl.co.jp **DIGI INTERNATIONAL SINGAPORE** +65-6213-5380

**DIGI INTERNATIONAL CHINA** +86-21-50492199 / www.digi.com.cn

