



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





RFID

Type A NFC RFID Inlay

**AD-709x**

**Dimensions** 1.85 x 1.85 in [47 x 47 mm]  
**Operating Frequency** 13.56 MHz  
**RF Protocol** ISO-15693, 18000-3 Mode 1  
**Chip** NXP ICODE SLIX  
**User Memory** 896-bit EEPROM Read/Write

**Common Applications**

Library  
 Print Media  
 Documents & Files

Toll free US 866-903- RFID (7343) / [rfid.info@averydennison.com](mailto:rfid.info@averydennison.com)  
 International +1-770-965-0807

PART NUMBER	RF700037	RF700038	RF750016
Format	Dry Inlay	PS Inlay	Paper Label
Antenna dimensions (CDxMD)	1.85 x 1.85 in [47 x 47mm]	1.85 x 1.85 in [47 x 47mm]	1.85 x 1.85 in [47 x 47mm]
Die-cut dimensions	N/A	2 x 2 in [50 x 50 mm]	2 x 2 in [50 x 50 mm]
Inlay substrate material	PET	PET	PET
Inlay-to-liner adhesive	N/A	S490 (Fasson)	S490 (Fasson)
Liner material	N/A	40# SCK	40# SCK
Face Sheet	N/A	N/A	47.8# TT 1C (Fasson)
Standard pitch	2.125 in (54 mm)	2.125 in (54 mm)	2.125 in (54 mm)
Standard web width	2.125 in (54 mm)	2.125 in (54 mm)	2.125 in (54 mm)
Total thickness over chip	8.7 – 10.7 mils (221 – 272 µm)	11.9 – 13.9 mils (302- 353 µm)	15.1 – 17.1 mils (384 – 434 µm)
Operating temperature	-40° to 185 °F (-40° to 85 °C)	-40° to 185 °F (-40° to 85 °C)	-40° to 185 °F (-40° to 85 °C)
RoHS	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant	EU Directive 2011/65/EU Compliant
Quality assurance	100% read tested with out-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked	100% read tested with-of-tolerance inlay marked
Un-wind direction	Inlay-side Out	Inlay-side Out	Inlay-side Out
Core size with adaptor insert	3 in (76.2 mm)	3 in (76.2mm)	3 in (76.2 mm)
Maximum roll outer diameter (not to exceed)	13 in (330.2 mm)	13 in (330.2 mm)	7.48 in (190 mm)
Average # of units per roll	5,000	5,000	1,500 verified
Rev	01	01	00

**Care and handling:** RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

**Applications:** This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Avery Dennison does not represent that this product is fit for any particular purpose or use.

**Warranty:** Please refer to Avery Dennison RFID standard terms and conditions.

**Product Information:** Avery Dennison reserves the right to modify, change, supplement or discontinue product offerings at any time without notice. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

**Trademark statement:** Avery Dennison, S490 and Fasson are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit [www.rfid.averydennison.com](http://www.rfid.averydennison.com).