Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

**Documentation**
   Installation Guide

**Applications**
   Hardware debug
   Software debug
   Flash Programming

**Warranty:** 1 year from date of purchase for emulator and power supply, for Code Composer refer to the TI website

**Part #:** 701124

### SPI530 MPSD Intelligent Emulator with Code Composer for TMS320C3x/C4x



SPI530 Intelligent MPSD Emulator

| Hardware Features | Software Features | What's Included |
|---|---|---|
| • Supports Texas Instruments TMS320C30/31/32 Digital Signal Processors with MPSD interface | • Compatible with Windows based Code Composer from Texas Instruments | • SPI530 Emulator |
| • Provides highest performance with internal high speed control processor | • Compatible with Win 98 ME, NT, 2000, XP | • +5 Volt power supply |
| • Compatible with XDS510 ISA MPSD emulator from Texas Instruments | | • Parallel port cable |
| • Operates with parallel port, no internal adapter card required | | • CD-ROM with Code Composer for TMS320C3x/C4x |
| • Compatible with portable and laptop PCs | | • CD-ROM with drivers for emulator |
| • Six LEDs for operational status | | |
| • Compatible with +3.3V or +5V processors | | |
| • Power by supplied AC adapter | | |