



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



7018X Series Bicolor SMT LEDs

Description and Features



Color Combinations:

- Red/Green
- Green/Yellow

Surface Mount Technology

- Tape and reel packaged for high-speed autoinsertion.
- Convection and vapor-phase reflow compatible.
- Compact form enables high density placement.
- Packaged 4000 per reel.

Leading Edge LED Optoelectronic Performance

- Consistent high brightness.

Exceptional Reliability

- Stringent process controls assure quality.
- Extensive qualification testing to meet strictest requirements.
- Designed to permit easy post-reflow solder joint inspection.

- Refer to "Solder Pad Geometry 1.pdf"

Electro-Optical Characteristics and Ratings

PART NUMBER	7018X1/5	7018X5/7
Output Color	Red/Green	Green/Yellow
Diffusion	Diffused	Diffused
Package Color	Clear	Clear
Test Current (mA)	20	20
Forward Voltage Typ. (V)	2.1	18
Forward Voltage Max. (V)	2.8	28
Luminous Intensity Min. (mcd)	4.5	9
Luminous Intensity Typ. (mcd)	6.4	16
Luminous Intensity Max. (mcd)	-	-
Peak Wavelength (nm)	560	580
Viewing Angle (degrees)	120	110
Power Dissipation (mW)	70	70
Storage Temperature (°C)	-40 to +100	-40 to +100
Operating Temperature (°C)	-30 to +85	-30 to +85
Peak Forward Current Max. (1μs @ 0% duty cycle) (mA)	60	60
Reverse Voltage (IR=100μA) (V)	4	4
Lead Solder Time @260°C	5	5