

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Saws & Blades

Saws and blades from Klein are designed with the professional user in mind, providing superior results with less effort.

For Professionals.. Since 1857™



Saws & Blades

High-Tension Hacksaw

- Adjustable blade tension up to 30,000 PSI for fast, precise cuts
- Soft-touch grips
- Alternative 45° mounting for flush cutting
- Front mount for reciprocating saw blades
- Blade storage in handle
- Includes 12" x 24 TPI bi-metal hack saw blade and 6" x 24 TPI bi-metal reciprocating saw blade

Cat. No.	Blade Length	Overall Length	Weight	
702-12	12" (304.8 mm)	16-1/4" (412.8 mm)	1.5 lbs. (0.68 kg)	



702-12

Dual-Purpose Hacksaw - Golden Tri-Cut™ 3-in-1 Blade

- Blade has three teeth sizes
- Blade converts quickly to 90° or 45° for standard or flush-cut applications
- Pivot-lock adjusts blade tension for straighter cuts and longer blade life
- Set screw allows for storage of extra blades and secures blade for "jab" sawing
- Aluminum finger grip handle and front end
- Thumb guard for two-hand sawing

Cat. No.	Blade Length	Overall Length	Weight
701-S	12" (304.8 mm)	16" (406.4 mm)	1.5 lbs. (0.68 kg)





701-S

Bi-Metal Blades



1224BI

- Special high-speed steel teeth fused to regular carbon-steel body, which provides superior cutting and longer life
- Withstands greater saw tension for less blade flexing
- Fits all 12" (305 mm) hacksaw blades
- Available in box of 100 blades or in a reclosable, heavy-vinyl, seal-tight pouch of 10 blades

Cat. No.	Teeth Per Inch	Overall Length	Package Quantity	Weight
1218BI-P	18	12" (304.8 mm)	10-Pack	7.2 oz. (204 g)
1224BI-P	24	12" (304.8 mm)	10-Pack	7.2 oz. (204 g)
1232BI-P	32	12" (304.8 mm)	10-Pack	7.2 oz. (204 g)
1218BI	18	12" (304.8 mm)	100-Pack	4.5 lbs. (2.04 kg)
1224BI	24	12" (304.8 mm)	100-Pack	4.5 lbs. (2.04 kg)
1232BI	32	12" (304.8 mm)	100-Pack	4.5 lbs. (2.04 kg)

Golden Tri-Cut™ Blades

SECURITY CAT NO 120881 WESTERN KLEIN TOOLS SOLDEN THEOUT

1200BI




Blade has three teeth sizes

- Unique design provides three teeth sizes on one blade
- Has 32 teeth/inch up front for quick starts, 24 teeth/inch in the middle and 18 teeth/inch on the end for fast and smooth conventional cutting
- Special high-speed steel teeth fused to carbon-steel provide superior cutting action and long life
- Gold finish
- Available in box of 100 blades or in a reclosable, heavy-vinyl, seal-tight pouch of 10 blades

Cat. No.	Teeth Per Inch	Overall Length	Package Quantity	Weight
1200BI-P	32-24-18	12" (304.8 mm)	10-Pack	7.2 oz. (204 g)
1200BI	32-24-18	12" (304.8 mm)	100-Pack	4.5 lbs. (2.04 kg)







Saws & Blades

Jab Saw

- Cuts drywall, wallboard, plywood and plastic
- Triple ground teeth for a fast cut
- Blade cuts in both directions (push and pull)
- Hardened, carbon-steel blade for durability
- Hardened, beveled blade point for scoring and plunge cuts
- Comfort cushion grip with thumb groove
- Handle structure designed for strength and durability
- Flat-end grip for palming or punching through drywall



725

Cat. No.	Blade Length	Overall Length	Weight
725	6" (152.4 mm)	12" (304.8 mm)	5.0 oz. (142 g)

Magic-Slot Compass Saws

- Magic-Slot design allows fast blade changing without removing thumbscrew
- Strong, lightweight, die-cast zinc handle with blue finish is contoured for comfort
- Cat. No. 703 comes with Cat. No. 706 8" blade
- Blade is tough, high-quality carbon steel, 8" (203 mm) long, with ten teeth per inch for general-purpose use
- Cat. No. 702 can be used with Magic-Slot cut-in or general-purpose blades only
- Replacement blades and handle can be ordered separately



703

Cat. No.	Description	Teeth Per Inch	Overall Length	Weight
703	Magic-Slot Compass Saw with 8" Blade	10	13" (330.2 mm)	1.2 lbs. (0.54 kg)
702	Magic-Slot Compass Saw Handle	_	5" (127.0 mm)	1.1 lbs. (0.50 kg)

Compass Saw Replacement Blades

- For cutting through wallboard or Masonite to install wiring, outlet boxes, etc.
- Tough high-quality carbon steel
- Pointed starter tip
- Fits Magic-Slot compass saw handle Cat. No. 702



709

Cat. No.	Teeth Per Inch	Overall Length	Weight 2.2 oz. (62 g) 2.2 oz. (62 g)	
704	8	12" (304.8 mm)		
705	10	12" (304.8 mm)		
706	10	8" (203.2 mm)	1.4 lbs. (0.64 kg)	
707	10	10" (254.0 mm)	1.9 oz. (54 g)	
709	10	4" (101.6 mm)	1.0 oz. (28 g)	

Reciprocating Saw Blades

- Bi-metal blades for different cutting applications of steel and wood
- Shock resistant teeth resist strippage
- 1/2" universal shank to fit all popular reciprocating saw tools

NOTE: Read and follow safety instructions in power tool owner's manual.



31716



31728

Cat. No.	Teeth Per Inch	Blade Length	Blade Width	Blade Thickness	Application	Package Quantity	Weight
31716	6	6" (152.4 mm)	3/4" (19.1 mm)	0.050" (1.27 mm)	Wood with Nails	5-Pack	3.6 oz. (102 g)
31728	18	6" (152.4 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	Heavy Gauge Metals	5-Pack	6.5 oz. (184 g)
31734	24	6" (152.4 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	18 Gauge and Under	5-Pack	1.6 oz. (45 g)







