

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








Push Button Switches

			CATALOG NUMBER			
			TYPE OF TERMINATION			
			.187		.250	SOLDER
RATINGS	CIRCUIT	ACTION	Q.C.	SCREW	Q.C.	LUG

7100 SERIES PUSHBUTTON

	SPST	PUSH ON	PUSH OFF	7104A	7104B	7104C	7104D
6A-125VAC		OFF	(ON)	7174A	7174B	7174C	7174D
3A-250VAC		ON	(OFF)	7184A	7184B	7184C	7184D
Α	SPDT	PUSH ON	PUSH ON	7103A	7103B	7103C	7103D
		ON	(ON)	7173A	7173B	7173C	7173D



7 SERIES L.P.

7000 SERIES PUSHBUTTON

	SPST	PUSH ON	PUSH OFF	7004A	7004B	7004C	7004D
15A-125VAC		OFF	(ON)	7074A	7074B	7074C	7074D
10A-125VAC		ON	(OFF)	7084A	7084B	7084C	7084D
	SPDT	PUSH ON	PUSH ON	7003A	7003B	7003C	7003D
		ON	(ON)	7073A	7073B	7073C	7073D

) Denotes Momentary

Specify Metal Or Nylon Actuator To Obtain Metal Low Profile Actuation Add L.P. To P/N.

SPECIFICATIONS

Agency Listings

SA Certified

Contact Mechanism

Slow-Make/Slow-Break Butt Contact

Contact Material

7100 Series:

Stationary-Copper Alloy/Silver Plated

Movable-Copper Alloy

7000 Series:

Stationary (Center)-Copper Alloy/Silver Plated Stationary (End)-Silver Cadmium Oxide Composite

Movable-Silver Cadmium Oxide Composite

Dielectric Strength

1000 Volts RMS Minimum

Mounting Means

15/32" Diameter Threaded Bushing

Keyway .080-.083 Wide X .032-.038 Deep Standard Hardware Supplied -

One Hex Nut Assembled And

One Hex Nut Unassembled

Switch Hardware













#42-06 Hex Nut #42-04 Knurled Nut #34-08 Lockwasher #52-08 ON-OFF Plate #52-30 HI-LO Plate #34-13 Locking Ring

CATALOG NUMBER	DESCRIPTION	SPECIFICATIONS	FINISH
42-06	HEX NUT	.562 O.D., .074 THICK	NICKEL
42-04	KNURLED NUT	.605 O.D., .100 THICK	NICKEL
34-08	LOCKWASHER	.600 O.D., .018 THICK	NICKEL
52-08	ON-OFF PLATE	.025 THICK	NICKEL
52-30	HI-LO PLATE	.025 THICK	NICKEL
34-13	LOCKING RING	.718 O.D., .040 THICK	ZINC

All Of The Above Hardware Fits A 15/32-32 Bushing