



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Common Mode EMI Chokes




Special Features

- Reduce conductive EMI emission
- High current capacity
- High impedance at low frequency
- Dielectric strength 3750 Vrms
- Coil wound on UL 94V-0 rated plastic cased ferrite core
- Operating temperature -55 to +105 °C

† RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

| 7100 Series | | | | | | | | |
|-------------|---------------------------|--------------|--------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Part Number | L (mH) Min. @ 1 KHz | I, DC (A) | DCR (Ω) Max. | Dim. A Max. | Dim. B Max. | Dim. C Nom. | Dim. D Nom. | Dim. E Nom. |
| 7101-RC | 0.51 | 1.0 | 0.040 | 0.70 | 0.55 | 0.400 | 0.200 | 0.016 |
| 7102-RC | 0.85 | 1.0 | 0.060 | 0.70 | 0.55 | 0.400 | 0.200 | 0.016 |
| 7103-RC | 1.70 | 1.0 | 0.070 | 0.70 | 0.55 | 0.400 | 0.200 | 0.016 |
| 7104-RC | 2.55 | 1.0 | 0.100 | 0.70 | 0.55 | 0.400 | 0.200 | 0.016 |
| 7105-RC | 4.25 | 1.0 | 0.125 | 0.70 | 0.55 | 0.400 | 0.200 | 0.016 |
| 7106-RC | 0.51 | 2.0 | 0.030 | 0.70 | 0.55 | 0.400 | 0.200 | 0.020 |
| 7107-RC | 0.85 | 2.0 | 0.040 | 0.70 | 0.55 | 0.400 | 0.200 | 0.020 |
| 7108-RC | 1.70 | 2.0 | 0.060 | 0.70 | 0.55 | 0.400 | 0.200 | 0.020 |
| 7109-RC | 2.55 | 2.0 | 0.075 | 0.70 | 0.55 | 0.400 | 0.200 | 0.020 |
| 7110-RC | 0.51 | 3.0 | 0.020 | 0.70 | 0.55 | 0.400 | 0.200 | 0.023 |
| 7111-RC | 0.85 | 3.0 | 0.030 | 0.70 | 0.55 | 0.400 | 0.200 | 0.023 |
| 7112-RC | 0.85 | 2.0 | 0.050 | 0.90 | 0.65 | 0.500 | 0.300 | 0.023 |
| 7113-RC | 1.70 | 2.0 | 0.075 | 0.90 | 0.65 | 0.500 | 0.300 | 0.023 |
| 7114-RC | 2.55 | 2.0 | 0.085 | 0.90 | 0.65 | 0.500 | 0.300 | 0.023 |
| 7115-RC | 4.25 | 2.0 | 0.110 | 0.90 | 0.65 | 0.500 | 0.300 | 0.023 |
| 7116-RC | 6.80 | 2.0 | 0.200 | 0.90 | 0.65 | 0.500 | 0.300 | 0.023 |
| 7117-RC | 0.85 | 5.0 | 0.035 | 0.90 | 0.65 | 0.500 | 0.300 | 0.030 |
| 7118-RC | 1.70 | 5.0 | 0.040 | 1.23 | 0.90 | 0.700 | 0.400 | 0.030 |
| 7119-RC | 4.25 | 4.0 | 0.046 | 1.23 | 0.90 | 0.700 | 0.400 | 0.030 |
| 7120-RC | 6.80 | 4.0 | 0.060 | 1.23 | 0.90 | 0.700 | 0.400 | 0.030 |
| 7121-RC | 42.5 | 2.0 | 0.200 | 1.23 | 0.90 | 0.700 | 0.400 | 0.023 |
| 7122-RC | 25.5 | 4.0 | 0.130 | 1.23 | 0.90 | 0.700 | 0.400 | 0.030 |
| 7123-RC | 9.35 | 5.0 | 0.072 | 1.23 | 0.90 | 0.700 | 0.400 | 0.036 |
| 7124-RC | 2.55 | 10 | 0.020 | 1.23 | 0.90 | 0.700 | 0.400 | 0.046 |

“-RC” suffix indicates RoHS compliance.



Dimensions: Inches

