

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










SINGLE-IN-LINE SOCKETS **Ultra Low Profile Carriers** Single and Double Row



- Ultra low profile receptacles sit .018" above the board.
- Series 714 uses M-M# 0552-1, 0552-2 pin receptacles. See page 127 for details.
- Hi-Rel, 3-finger BeCu #11 clip is rated at 3amps. See page 206 for details.




Fig. 1




Fig. 2 Number of Pins X .100" / 2 |-

ooooollooooo





Fig. 3



Ordering Information

Fig. 1	714-XX-131-012	
	Specify # of pins 01-64	

Single Row (.039 min. mounting hole)

Single Row (.039 min. mounting hole)

Fig. 2	/14-XX-131-018		
	Specify # of pins		01-64

Double Row (.039 min. mounting hole)

04 040

Fig. 3	/ 14-XX-2 __	31-01	2	
	Specify # of pins	_	02-64	

Double Row (.039 min. mounting hole)

Fig. 4	714-XX-2_	31-018	3	
	Specify # of pins	>	02-64	



SPECIFY PLATING CODE XX=	93 99
Sleeve (Pin)	200μ" Sn/Pb 200μ" Sn/Pb
Contact (Clip)	30μ" Au 200μ"Sn/Pb