mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Technical Data Sheet

Models 7158 , 7159, 7160 1/4" 2 & 3-Cond. Phone Jack, PC Board Mount



Model 7158 Horizontal 3-Conductor Jack, PC Board Mount

Ordering Information

Model: 7158, 7159, 7160



Model 7159 Horizontal 2-Conductor Jack, PC Board Mount



Model 7160 Horizontal 3-Conductor Jack, Solder Tabs

Use to mount securely with PC boards.

Features

- Connects with standard commercial phone plugs
- PC board mountable
- Stereo and mono versions
- Solderable
- 2 and 3 conductor versions

Materials

- Shell: Polyamide 6.6 15% GR
- Contacts: Nickel silver

 USA:
 Sales:
 800-490-2361
 Technical Support:
 800-241

 2060
 Fax:
 888-403-3360
 International:
 425-446-5500

 e-mail:
 technicalsupport@pomonatest.com
 International:
 425-446-5500

Where to Buy: www.pomonaelectronics.com

Specifications

| Number of conductors | 2 (Mono)-Model 7159 3 (Stereo)-Models 7158, 7160 |
|------------------------|--|
| Contact resistance | < 15 mΩ |
| Dielectric strength | 1000 V dc |
| Insulations Resistance | 1000 ΜΩ |

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02^{\circ}$ (,51 mm), $.xxx = \pm .005^{\circ}$ (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.