

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Technical Data Sheet		Rosenberger		
BNC 75 Ω	Calibration Kit Industrial Version	71CK010-170		



Picture shows similar calibration kit

# **Contents**

Device	Part number	Quantity	Calibration Option <sup>a</sup>	
Open circuit plug	71S12L-000S3	1	FC	
Open circuit jack	71K12L-000S3	1	FC	
Short circuit plug	71S12S-000S3	1	FC	
Short circuit jack	71K12S-000S3	1	FC	
Calibration load plug	71S170-C10S3	1	FC	
Calibration load jack	71K170-C10S3	1	FC	
Calibration adaptor plug/plug	71S121-S20S3	1	FC	
Calibration adaptor jack/jack	71K121-K20S3	1	FC	

a. See "Declaration of calibration options" for explanation.

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : <u>info@rosenberger.de</u> Page

1/3

Technical Data Sheet		Rosenberger		
BNC 75 Ω	Calibration Kit Industrial Version	71CK010-170		

#### **Documentation**

This kit is delivered with

USB-Stick

Standard Definitions as data files for Vector Network Anaylzer Families PNA (Keysight/Agilent) and ZVA (Rohde&Schwarz). Calibration Certificate as PDF-file.

- Standard Definitions Cards
  - Printed Standard Definitions that can be used on nearly all Vector Network Analyzers.
- Kit Info Card
  - Handling precautions and information for installing Standard Definitions on a Vector Network Analyzer.
- Calibration Certificate
  - Details see "Declaration of calibration options"
- Operating Manual

## **Electrical specifications**

This specification covers electrical key values for the main calibration standards of the calibration kit. Specific datasheets are available for each component among the part number.

Calibration standard	Frequency	Parameter	Specification	
Opens <sup>b</sup> (plug and jack)	DC to ≤2 GHz	Error from	≤ 3.0°	
	> 2 GHz to ≤4 GHz	Nominal Phase	≤ 5.0°	
Shorts <sup>b</sup> (plug and jack)	DC to ≤2 GHz	Error from	≤ 2.5°	
	> 2 GHz to ≤4 GHz	Nominal Phase	≤ 4.0°	
Calibration loads	DC to ≤2 GHz	Return Loss	≥ 35 dB	
(plug and jack)	> 2 GHz to ≤4 GHz		≥ 30 dB	
Calibration adaptors	DC to ≤2 GHz	Return Loss	≥ 34 dB	
(plug/plug and jack/jack)	> 2 GHz to ≤4 GHz		≥ 30 dB	

b. The specifications for opens and shorts are given as allowed deviation from nominal model as defined in calibration certificate included with your kit.

Tel.

2/3

: +49 8684 18-0

Technical Data Sheet		Rosenberger		
BNC 75 Ω	Calibration Kit Industrial Version	71CK010-170		

## Declaration of calibration options

### **Factory Calibration**

Standard delivery for this kit includes a Factory Calibration. The Calibration Certificate issued reports individual calibration results, **traceable to Rosenberger standards**, national / international standards are not available. Model based standard definitions of the calibration standards are reported in Agilent/Keysight, Rohde & Schwarz and Anritsu compatible VNA format.

#### **Accredited Calibration**

Not available.

For further, more detailed information see application note AN001 on the Rosenberger homepage.

### Calibration interval

Recommendation

12 months

#### Recommended accessories

- Rosenberger Calibration Adaptor RPC-N 75 Ohm female to BNC 75 Ohm female P5K171-K2AS3
- Rosenberger Calibration Adaptor RPC-N 75 Ohm female to BNC 75 Ohm male P5K171-S2AS3
- Rosenberger Calibration Adaptor RPC-N 75 Ohm male to BNC 75 Ohm female P5S171-K2AS3
- Rosenberger Calibration Adaptor RPC-N 75 Ohm male to BNC 75 Ohm male P5S171-S2AS3
- Rosenberger Test Port Adaptor
- Rosenberger VNA Test cable kit and Microwave Cable Assemblies

For further, more detailed information please visit our homepage <u>www.rosenberger.com</u>.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

				_				
Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
Herbert Babinger	30.07.15	Martin Moder	16.09.15		b00	14-1492	Maik Knoll	16.09.15
Rosenberger Ho	Rosenberger Hochfrequenztechnik GmbH & Co. KG  Tel. : +49 8684 18-0						Page	
P.O.Box 1260 D-84526 Tittmoning Germany				Fa	x : +49 8684 18-499			
www.rosenberger.de				En	nail : info@rosenberger.de		3/3	