

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









FLIR TG167 (Global)

P/N: 74701-0104

Copyright

© 2016, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 74701-0104

Release: Commit: 33482 Language:

Modified: 2016-02-18 Formatted: 2016-02-18

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description

FLIR's new TG167 imaging infrared (IR) thermometer bridges the gap between single-spot IR thermometers and FLIR's legendary thermal cameras. Equipped with FLIR's exclusive Lepton micro thermal camera, the FLIR TG167 shows you where potential problems are brewing and where to aim your spot.

The FLIR TG167 lets you see heat patterns, reliably measure temperature, and store images and data. Its menu uses intuitive icons, making it simple to operate. The FLIR TG167 also makes documentation easy by saving images you can download from the Micro SD card or over a USB connection and use for reports.

Key features

- · See the heat and speed up troubleshooting.
- · Know where to measure temperature.
- · Grab and go simplicity—no special training required.
- Pocket portable to fit a crowded tool bag.
- Rugged and reliable.

Imaging and optical data		
IR resolution	80 × 60 pixels	
Thermal sensitivity/NETD	< 150 mK	
Field of view (FOV)	25° × 19.6°	
Minimum focus distance	0.1 m (4 in.)	
Distance to spot ratio	24:1	
Image frequency	9 Hz	
Focus	Focus free	
Detector data		
Detector type	Focal plane array (FPA), uncooled	

Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	8–14 μm

1 (4) www.flir.com



FLIR TG167 (Global)

P/N: 74701-0104

© 2016, FLIR Systems, Inc. #74701-0104; r. /33482;

Image precentation	Ι
Image presentation	2.0 in, TFT LCD
Display	2.0 III. 1F1 LCD
Measurement	
Object temperature range	-25 to +380°C (-13 to +716°F)
Accuracy	±1.5% or 1.5°C (2.7°F)
Minimum measurement distance	26 cm (10 in.)
Measurement analysis	
Center spot	Yes
Color palettes	Hot Iron Rainbow Grayscale
Set-up	
Set-up commands	Local adaptation of units, language, date, and time formats Deletion of images
Emissivity correction	4 pre-set levels with custom adjustment of 0.1–0.99
Storage of images	
Memory type	Micro SD card
Image storage capacity	75 000 pictures with included 8 GB Micro SD card
Memory expansion	32 GB SD card maximum
Saved image format	Bitmap (BMP) image with temperature and emissivity
Laser pointers	
Laser	Dual diverging lasers indicate the temperature measurement area, activated by pulling the trigger
Power system	
Battery type	Rechargeable Li ion battery
Battery voltage	3.7 V
Battery operating time	>5 hours of continuous scanning with lasers
Battery charge life	30 days minimum
Charging system	Battery is charged inside the camera
Charging time	4 hours to 90%, 6 hours to 100%
Power management	Adjustable: off, 1 minute, 2 minutes, 5 minutes, 10 minutes
Environmental data	
Operating temperature range	-10 to +45°C (+14 to 113°F)
Storage temperature range	−30 to +55°C (−22 to 131°F)



FLIR TG167 (Global)

P/N: 74701-0104

© 2016, FLIR Systems, Inc. #74701-0104; r. /33482;

Environmental data	
Humidity (operating and storage)	0–90% relative humidity (RH) (0–37°C (32–98.6° F)), 0–65% RH (37–45°C (98.6–113°F)), 0–45% RH (45–55°C (113–131°F))
EMC	 WEEE 2012/19/EC RoHs 2011/65/EC EN 61000-6-3 EN 61000-6-2 FCC 47 CFR Part 15 Class B
Magnetic fields	EN 61000-4-8
Encapsulation	IP 40 (IEC 60529)
Shock	25 g (IEC 60068-2-29)
Vibration	2 g (IEC 60068-2-6)
Drop	Designed for 2 m (6.6 ft.)
Safety	CE, FCC, PSC, FDA
Physical data	
Camera weight, incl. battery	0.312 kg (11 oz.)
Camera size $(L \times W \times H)$	186 mm × 55 mm × 94 mm (7.3 in. × 2.2 in. × 3.7 in.)
Tripod mounting	1/4 in20 on handle bottom
Color	Black, white, silver
Material	PC-ABS, TPU
Shipping information	
Packaging, type	Color box with view of product in clamshell
List of contents	Imaging IR thermometer 8 GB Micro SD card Printed documentation Wrist strap lanyard Power supply with separate USB cable
Packaging, weight	0.85 kg (1.8 lb.)
Packaging, size	$34 \text{ cm} \times 15 \text{ cm} \times 12 \text{ cm} (13.5 \text{ in.} \times 6 \text{ in.} \times 4.5 \text{ in.})$
EAN-13	7332558010877
UPC-12	845188011628
Country of origin	China

3 (4) www.flir.com

