



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



74ACT16543

16-Bit Registered Transceiver with 3-STATE Outputs

General Description

The ACT16543 contains sixteen non-inverting transceivers containing two sets of D-type registers for temporary storage of data flowing in either direction. Each byte has separate control inputs which can be shorted together for full 16-bit operation. Separate Latch Enable and Output Enable inputs are provided for each register to permit independent input and output control in either direction of data flow.

Features


- Independent registers for A and B buses
- Separate controls for data flow in each direction
- Back-to-back registers for storage
- Multiplexed real-time and stored data transfers
- Separate control logic for each byte
- Outputs source/sink 24 mA
- TTL-compatible inputs

Ordering Code:


| Order Number | Package Number | Package Description |
|---------------|----------------|-----------------------------------------------------------------------------|
| 74ACT16543SSC | MS56A | 56-Lead Shrink Small Outline Package (SSOP), JEDEC MO-118, 0.300" Wide |
| 74ACT16543MTD | MTD56 | 56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide |

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code.

Logic Symbol



Connection Diagram



Pin Descriptions

| Pin Names | Descriptions |
|---------------------|-------------------------------------------------|
| \overline{OEAB}_n | A-to-B Output Enable Input (Active LOW) |
| \overline{OEBA}_n | B-to-A Output Enable Input (Active LOW) |
| \overline{CEAB}_n | A-to-B Enable Input (Active LOW) |
| \overline{CEBA}_n | B-to-A Enable Input (Active LOW) |
| \overline{LEAB}_n | A-to-B Latch Enable Input (Active LOW) |
| \overline{LEBA}_n | B-to-A Latch Enable Input (Active LOW) |
| A_0 - A_{15} | A-to-B Data Inputs or B-to-A 3-STATE Outputs |
| B_0 - B_{15} | B-to-A Data Inputs or A-to-B 3-STATE Outputs |

FACT™ is a trademark of Fairchild Semiconductor Corporation.

Functional Description


The ACT16543 contains sixteen non-inverting transceivers with 3-STATE outputs. The device is byte controlled with each byte functioning identically, but independent of the other. The control pins may be shorted together to obtain full 16-bit operation. The following description applies to each byte. For data flow from A to B, for example, the A-to-B Enable (\overline{CEAB}_n) input must be LOW in order to enter data from A_0 – A_{15} or take data from B_0 – B_{15} , as indicated in the Data I/O Control Table. With \overline{CEAB}_n LOW, a LOW signal on the A-to-B Latch Enable (\overline{LEAB}_n) input makes the A-to-B latches transparent; a subsequent LOW-to-HIGH transition of the \overline{LEAB}_n signal puts the A latches in the storage mode and their outputs no longer change with the A inputs. With \overline{CEAB}_n and \overline{OEAB}_n both LOW, the 3-STATE B output buffers are active and reflect the data present at the output of the A latches. Control of data flow from B to A is similar, but using the \overline{CEBA}_n , \overline{LEBA}_n and \overline{OEBA}_n inputs.

Data I/O Control Table

| Inputs | | | Latch Status (Byte n) | Output Buffers (Byte n) |
|---------------------|---------------------|---------------------|-----------------------|-------------------------|
| \overline{CEAB}_n | \overline{LEAB}_n | \overline{OEAB}_n | | |
| H | X | X | Latched | High Z |
| X | H | X | Latched | — |
| L | L | X | Transparent | — |
| X | X | H | — | High Z |
| L | X | L | — | Driving |

H = HIGH Voltage Level
 L = LOW Voltage Level
 X = Immaterial
 A-to-B data flow shown; B-to-A flow control is the same, except using \overline{CEBA}_n , \overline{LEBA}_n and \overline{OEBA}_n

Logic Diagrams



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings(Note 1)

| | |
|----------------------------------------------|--------------------------|
| Supply Voltage (V_{CC}) | -0.5V to +7.0V |
| DC Input Diode Current (I_{IK}) | |
| $V_I = -0.5V$ | -20 mA |
| $V_I = V_{CC} + 0.5V$ | +20 mA |
| DC Output Diode Current (I_{OK}) | |
| $V_O = -0.5V$ | -20 mA |
| $V_O = V_{CC} + 0.5V$ | +20 mA |
| DC Output Voltage (V_O) | -0.5V to $V_{CC} + 0.5V$ |
| DC Output Source/Sink Current (I_O) | ± 50 mA |
| DC V_{CC} or Ground Current per Output Pin | ± 50 mA |
| Storage Temperature | -65°C to +150°C |

Recommended Operating Conditions

| | |
|-------------------------------------------------|----------------|
| Supply Voltage (V_{CC}) | 4.5V to 5.5V |
| Input Voltage (V_I) | 0V to V_{CC} |
| Output Voltage (V_O) | 0V to V_{CC} |
| Operating Temperature (T_A) | -40°C to +85°C |
| Minimum Input Edge Rate ($\Delta V/\Delta t$) | 125 mV/ns |
| V_{IN} from 0.8V to 2.0V | |
| V_{CC} @ 4.5V, 5.5V | |

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation of FACT™ circuits outside databook specifications.

DC Electrical Characteristics


| Symbol | Parameter | V_{CC} (V) | $T_A = +25^\circ\text{C}$ | | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ | Units | Conditions |
|-----------|-----------------------------------------|-----------------|---------------------------|-------------------|-------------------------------------------------|---------|--------------------------------------------------------------------------------------------------|
| | | | Typ | Guaranteed Limits | | | |
| V_{IH} | Minimum HIGH Input Voltage | 4.5 | 1.5 | 2.0 | 2.0 | V | $V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$ |
| | | 5.5 | 1.5 | 2.0 | 2.0 | | |
| V_{IL} | Maximum LOW Input Voltage | 4.5 | 1.5 | 0.8 | 0.8 | V | $V_{OUT} = 0.1V$ or $V_{CC} - 0.1V$ |
| | | 5.5 | 1.5 | 0.8 | 0.8 | | |
| V_{OH} | Minimum HIGH Output Voltage | 4.5 | 4.49 | 4.4 | 4.4 | V | $I_{OUT} = -50 \mu A$ |
| | | 5.5 | 5.49 | 5.4 | 5.4 | | |
| | | 4.5 | | 3.86 | 3.76 | V | $V_{IN} = V_{IL}$ or V_{IH} $I_{OH} = -24 \text{ mA}$ $I_{OH} = -24 \text{ mA}$ (Note 2) |
| V_{OL} | Maximum LOW Output Voltage | 4.5 | 0.001 | 0.1 | 0.1 | V | $I_{OUT} = 50 \mu A$ |
| | | 5.5 | 0.001 | 0.1 | 0.1 | | |
| | | 4.5 | | 0.36 | 0.44 | V | $V_{IN} = V_{IL}$ or V_{IH} $I_{OL} = 24 \text{ mA}$ $I_{OL} = 24 \text{ mA}$ (Note 2) |
| I_{OZT} | Maximum I/O Leakage Current | 5.5 | | ± 0.5 | ± 5.0 | μA | $V_I = V_{IL}, V_{IH}$ $V_O = V_{CC}, \text{GND}$ |
| I_{IN} | Maximum Input Leakage Current | 5.5 | | ± 0.1 | ± 1.0 | μA | $V_I = V_{CC}, \text{GND}$ |
| I_{CCT} | Maximum I_{CC} /Input | 5.5 | 0.6 | | 1.5 | mA | $V_I = V_{CC} - 2.1V$ |
| I_{CC} | Max Quiescent Supply Current | 5.5 | | 8.0 | 80.0 | μA | $V_{IN} = V_{CC}$ or GND |
| I_{OLD} | Minimum Dynamic Output Current (Note 3) | 5.5 | | | 75 | mA | $V_{OLD} = 1.65V \text{ Max}$ |
| I_{OHD} | | | | | -75 | mA | $V_{OHD} = 3.85V \text{ Min}$ |

Note 2: All outputs loaded; thresholds associated with output under test.

Note 3: Maximum test duration 2.0 ms; one output loaded at a time.


| AC Electrical Characteristics | | | | | | | | |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------|---------------------------------|------|-----------------------------------------------------------|------|-------|
| Symbol | Parameter | V _{CC} (V) (Note 4) | T _A = +25°C C _L = 50 pF | | | T _A = -40°C to +85°C C _L = 50 pF | | Units |
| | | | Min | Typ | Max | Min | Max | |
| t _{PLH} | Propagation Delay | 5.0 | 3.8 | 5.9 | 8.3 | 3.0 | 9.0 | ns |
| t _{PHL} | Transparent Mode A _n to B _n or B _n to A _n | | 3.5 | 5.5 | 7.9 | 2.6 | 8.5 | |
| t _{PLH} | Propagation Delay | 5.0 | 4.7 | 6.9 | 9.8 | 3.4 | 10.8 | ns |
| t _{PHL} | \overline{LEBA}_n , \overline{LEAB}_n to A _n , B _n | | 3.9 | 6.3 | 9.0 | 3.1 | 9.8 | |
| t _{PZH} | Output Enable Time | 5.0 | 4.2 | 6.3 | 9.2 | 3.0 | 9.9 | ns |
| t _{PZL} | \overline{OEBA}_n or \overline{OEAB}_n to A _n or B _n \overline{CEBA}_n or \overline{CEAB}_n to A _n or B _n | | 4.9 | 7.3 | 10.3 | 3.6 | 10.3 | |
| t _{PHZ} | Output Disable Time | 5.0 | 2.8 | 5.2 | 8.0 | 2.1 | 8.3 | ns |
| t _{PLZ} | \overline{OEBA}_n or \overline{OEAB}_n to A _n or B _n \overline{CEBA}_n or \overline{CEAB}_n to A _n or B _n | | 2.6 | 5.0 | 7.6 | 2.0 | 8.1 | |
| Note 4: Voltage Range 5.0 is 5.0V ± 0.5V. | | | | | | | | |
| AC Operating Requirements | | | | | | | | |
| Symbol | Parameter | V _{CC} (V) (Note 5) | T _A = +25°C | T _A = -40°C to +85°C | | Units | | |
| | | | C _L = 50 pF | C _L = 50 pF | | | | |
| | | | Guaranteed Minimum | | | | | |
| t _S | Setup Time, HIGH or LOW A _n or B _n to \overline{LEBA}_n or \overline{LEAB}_n | 5.0 | 3.0 | 3.0 | 3.0 | ns | | |
| t _H | Hold Time, HIGH or LOW A _n or B _n to \overline{LEBA}_n or \overline{LEAB}_n | 5.0 | 1.5 | 1.5 | 1.5 | ns | | |
| t _W | Latch Enable, B to A Pulse Width, LOW | 5.0 | 4.0 | 4.0 | 4.0 | ns | | |
| Note 5: Voltage Range 5.0 is 5.0V ± 0.5V | | | | | | | | |
| Capacitance | | | | | | | | |
| Symbol | Parameter | Typ | Units | Conditions | | | | |
| C _{IN} | Input Capacitance | 4.5 | pF | V _{CC} = 5.0V | | | | |
| C _{PD} | Power Dissipation Capacitance | 95.0 | pF | V _{CC} = 5.0V | | | | |

Physical Dimensions inches (millimeters) unless otherwise noted



**56-Lead Thin Shrink Small Outline Package (SSOP), JEDEC MO-153, 6.1mm Wide
Package Number MS56A**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide Package Number MTD56

MTD56 (REV B)

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com