



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# 74ACT18825

## 18-Bit Buffer/Line Driver with 3-STATE Outputs

### General Description

The ACT18825 contains eighteen non-inverting buffers with 3-STATE outputs designed to be employed as a memory and address driver, clock driver, or bus oriented transmitter/receiver. The device is byte controlled. Each byte has separate 3-STATE control inputs which can be shorted together for full 18-bit operation.

### Features


- Broadside pinout allows for easy board layout
- Separate control logic for each byte
- Extra data width for wider address/data paths or buses carrying parity
- Outputs source/sink 24 mA
- TTL-compatible inputs

### Ordering Code:


| Order Number  | Package Number | Package Description   |
|---------------|----------------|---|
| 74ACT18825SSC | MS56A          | 56-Lead Shrink Small Outline Package (SSOP), JEDEC MO-118, 0.300" Wide      |
| 74ACT18825MTD | MTD56          | 56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide |

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering code.

### Logic Symbol



### Connection Diagram



### Pin Descriptions

| Pin Names                       | Description                      |
|---------------------------------|----------------------------------|
| OE <sub>n</sub>                 | Output Enable Input (Active LOW) |
| I <sub>0</sub> -I <sub>17</sub> | Inputs                           |
| O <sub>0</sub> -O <sub>17</sub> | Outputs                          |

FACT™, FACT Quiet Series™ and GTO™ are trademarks of Fairchild Semiconductor Corporation.

### Functional Description


The ACT18825 contains eighteen non-inverting buffers with 3-STATE standard outputs. The device is byte controlled with each byte functioning identically, but independently of the other. The control pins may be shorted together to obtain full 8-bit operation. The 3-STATE outputs are controlled by an Output Enable ( $\overline{OE}_n$ ) input for each byte. When  $\overline{OE}_n$  is LOW, the outputs are in 2-state mode. When  $\overline{OE}_n$  is HIGH, the outputs are in the high impedance mode, but this does not interfere with entering new data into the inputs.

### Truth Table

| Inputs            |                   |                   |                   | Outputs   |              |           |              |
|-------------------|-------------------|-------------------|-------------------|-----------|--------------|-----------|--------------|
| Byte 1 (0:8)      |                   | Byte 2 (8:17)     |                   | $I_0-I_8$ | $I_9-I_{17}$ | $O_0-O_8$ | $O_9-O_{17}$ |
| $\overline{OE}_1$ | $\overline{OE}_2$ | $\overline{OE}_3$ | $\overline{OE}_4$ |           |              |           |              |
| L                 | L                 | L                 | L                 | H         | H            | H         | H            |
| H                 | X                 | L                 | L                 | X         | L            | Z         | L            |
| X                 | H                 | L                 | L                 | X         | H            | Z         | H            |
| L                 | L                 | H                 | X                 | L         | X            | L         | Z            |
| L                 | L                 | X                 | H                 | H         | X            | H         | Z            |
| H                 | H                 | H                 | H                 | X         | X            | Z         | Z            |
| L                 | L                 | L                 | L                 | L         | L            | L         | L            |

H = HIGH Voltage Level  
 L = LOW Voltage Level  
 X = Immaterial  
 Z = HIGH Impedance

### Logic Diagram



**Absolute Maximum Ratings**(Note 1)

|   |                          |
|---|--------------------------|
| Supply Voltage ( $V_{CC}$ )             | -0.5V to +7.0V           |
| DC Input Diode Current ( $I_{IK}$ )     |                          |
| $V_I = -0.5V$                           | -20 mA                   |
| $V_I = V_{CC} + 0.5V$                   | +20 mA                   |
| DC Output Diode Current ( $I_{OK}$ )    |                          |
| $V_O = -0.5V$                           | -20 mA                   |
| $V_O = V_{CC} + 0.5V$                   | +20 mA                   |
| DC Output Voltage ( $V_O$ )             | -0.5V to $V_{CC} + 0.5V$ |
| DC Output Source/Sink Current ( $I_O$ ) | $\pm 50$ mA              |
| DC $V_{CC}$ or Ground Current           |                          |
| Per Output Pin                          | $\pm 50$ mA              |
| Storage Temperature                     | -65°C to +150°C          |

**Recommended Operating Conditions**

|   |                |
|---|----------------|
| Supply Voltage ( $V_{CC}$ )                     | 4.5V to 5.5V   |
| Input Voltage ( $V_I$ )                         | 0V to $V_{CC}$ |
| Output Voltage ( $V_O$ )                        | 0V to $V_{CC}$ |
| Operating Temperature ( $T_A$ )                 | -40°C to +85°C |
| Minimum Input Edge Rate ( $\Delta V/\Delta t$ ) | 125 mV/ns      |
| $V_{IN}$ from 0.8V to 2.0V                      |                |
| $V_{CC}$ @ 4.5V, 5.5V                           |                |

**Note 1:** Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. Fairchild does not recommend operation of FACT™ circuits outside databook specifications.

**DC Electrical Characteristics**

| Symbol    | Parameter                                  | $V_{CC}$<br>(V) | $T_A = +25^\circ\text{C}$ |                   | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ |         | Units  | Conditions |
|-----------|--|-----------------|---------------------------|-------------------|---|---------|--|------------|
|           |  |                 | Typ                       | Guaranteed Limits |   |         |  |            |
| $V_{IH}$  | Minimum HIGH<br>Input Voltage              | 4.5             | 1.5                       | 2.0               | 2.0   | V       | $V_{OUT} = 0.1V$<br>or $V_{CC} - 0.1V$   |            |
|           |  | 5.5             | 1.5                       | 2.0               | 2.0   |         |  |            |
| $V_{IL}$  | Maximum LOW<br>Input Voltage               | 4.5             | 1.5                       | 0.8               | 0.8   | V       | $V_{OUT} = 0.1V$<br>or $V_{CC} - 0.1V$   |            |
|           |  | 5.5             | 1.5                       | 0.8               | 0.8   |         |  |            |
| $V_{OH}$  | Minimum HIGH<br>Output Voltage             | 4.5             | 4.49                      | 4.4               | 4.4   | V       | $I_{OUT} = -50 \mu A$  |            |
|           |  | 5.5             | 5.49                      | 5.4               | 5.4   |         |  |            |
|           |  | 4.5             |                           | 3.86              | 3.76  | V       | $V_{IN} = V_{IL}$ or $V_{IH}$<br>$I_{OH} = -24 \text{ mA}$<br>$I_{OH} = -24 \text{ mA}$ (Note 2) |            |
|           |  | 5.5             |                           | 4.86              | 4.76  |         |  |            |
| $V_{OL}$  | Maximum LOW<br>Output Voltage              | 4.5             | 0.001                     | 0.1               | 0.1   | V       | $I_{OUT} = 50 \mu A$   |            |
|           |  | 5.5             | 0.001                     | 0.1               | 0.1   |         |  |            |
|           |  | 4.5             |                           | 0.36              | 0.44  | V       | $V_{IN} = V_{IL}$ or $V_{IH}$<br>$I_{OL} = 24 \text{ mA}$<br>$I_{OL} = 24 \text{ mA}$ (Note 2)   |            |
|           |  | 5.5             |                           | 0.36              | 0.44  |         |  |            |
| $I_{OZ}$  | Maximum 3-STATE<br>Leakage Current         | 5.5             |                           | $\pm 0.5$         | $\pm 5.0$                                       | $\mu A$ | $V_I = V_{IL}, V_{IH}$<br>$V_O = V_{CC}, \text{GND}$   |            |
| $I_{IN}$  | Maximum Input Leakage Current              | 5.5             |                           | $\pm 0.1$         | $\pm 1.0$                                       | $\mu A$ | $V_I = V_{CC}, \text{GND}$   |            |
| $I_{CCT}$ | Maximum $I_{CC}$ /Input                    | 5.5             | 0.6                       |                   | 1.5   | mA      | $V_I = V_{CC} - 2.1V$  |            |
| $I_{CC}$  | Maximum Quiescent Supply Current           | 5.5             |                           | 8.0               | 80.0  | $\mu A$ | $V_{IN} = V_{CC}$ or GND   |            |
| $I_{OLD}$ | Minimum Dynamic<br>Output Current (Note 3) | 5.5             |                           |                   | 75  | mA      | $V_{OLD} = 1.65V \text{ Max}$  |            |
| $I_{OHD}$ |  |                 |                           |                   | -75   | mA      | $V_{OHD} = 3.85V \text{ Min}$  |            |

**Note 2:** All outputs loaded; thresholds associated with output under test.

**Note 3:** Maximum test duration 2.0 ms, one output loaded at a time.

## AC Electrical Characteristics


| Symbol           | Parameter         | V <sub>CC</sub><br>(V)<br>(Note 4) | T <sub>A</sub> = +25°C<br>C <sub>L</sub> = 50 pF |     |     | T <sub>A</sub> = -40°C to +85°C<br>C <sub>L</sub> = 50 pF |      | Units |
|------------------|-------------------|------------------------------------|--|-----|-----|---|------|-------|
|                  |                   |                                    | Min  | Typ | Max | Min   | Max  |       |
| t <sub>PHL</sub> | Propagation Delay | 5.0                                | 2.0  | 5.3 | 8.4 | 2.0   | 9.0  | ns    |
| t <sub>PLH</sub> | Data to Output    |                                    | 2.0  | 5.6 | 8.7 | 2.0   | 9.2  |       |
| t <sub>PZL</sub> | Output Enable     | 5.0                                | 2.0  | 6.3 | 9.6 | 2.0   | 10.3 | ns    |
| t <sub>PZH</sub> | Time              |                                    | 2.0  | 6.5 | 9.7 | 2.0   | 10.4 |       |
| t <sub>PLZ</sub> | Output Disable    | 5.0                                | 1.5  | 4.5 | 7.3 | 1.5   | 7.6  | ns    |
| t <sub>PHZ</sub> | Time              |                                    | 1.5  | 5.1 | 8.5 | 1.5   | 8.8  |       |

Note 4: Voltage Range 5.0 is 5.0V ± 0.5V.

## Capacitance


| Symbol          | Parameter                     | Typ | Units | Conditions             |
|-----------------|-------------------------------|-----|-------|------------------------|
| C <sub>IN</sub> | Input Pin Capacitance         | 4.5 | pF    | V <sub>CC</sub> = 5.0V |
| C <sub>PD</sub> | Power Dissipation Capacitance | 95  | pF    | V <sub>CC</sub> = 5.0V |

**Physical Dimensions** inches (millimeters) unless otherwise noted



**56-Lead Shrink Small Outline Package (SSOP), JEDEC MO-118, 0.300" Wide  
Package Number MS56A**

**Physical Dimensions** inches (millimeters) unless otherwise noted (Continued)



**56-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide Package Number MTD56**

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

**LIFE SUPPORT POLICY**

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

[www.fairchildsemi.com](http://www.fairchildsemi.com)