



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# INDASH by PANAVISE®

I-75139-804

Page 1 of 1

## MOUNTING LOCATION:

Above center Air Vent V U

## TOOLS REQUIRED:

T-25 Torx Driver

Phillips Screwdriver

## HARDWARE INCLUDED:

S7-1847 & S7-1848 TOP's

W/(2)-O- 8/32" Acorn Nuts

(1)-A #8 x 9/16" Needle Pt. Screw

## CELL PHONE & MEDIA MOUNT

## INSTALLATION INSTRUCTIONS

PART#: 75139-804

MFG: VOLVO

MODELS & YEARS:

Volvo Semi- VN & VT-Series 02-2014

VHD 2002-2014

## \*\* ADVISEMENT \*\*

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

STEP #1: Open cup holder at top of dash. With T-25 Torx Driver remove the (2) screws located under the cup holder openings.

STEP #2: Lift up on the front of the bezel and tilt up the panel that includes the cup holder to release a total of (6) clips. Set panel aside.

STEP #3: Place Part A over the left side flat area and locate the left back screw of the bracket that holds the fuse panel in place. Remove this T-25 screw. Place the mount mounting hole over the screw hole, and replace the screw. The mount will come out just above the air vent. Make sure the mount fits well up to the front of the panel cavity, and that the slots for the clips of the bezel align to allow the top to fit in place. Install the (1) supplied Phillips Screw.

STEP #4: Pick which mount Top you want to install according to the device you are installing. The top with (1) bend fits in a North direction. And the (2) bend part fits with the face going in a South direction.

INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW INDASH by PANAVISE MOUNT.



T-25 Screw Locations



Tilting and Removal of Top



InDash installed showing North direction



InDash installed showing South direction



02-20-13