



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AC Power Supply - 12VDC,
extended temp. NEMA 5-15P (US)
to 2.1mm locking barrel plug.
Compatibility: Digi TransPort
WR41 (locking power cord
models), Digi Connect WAN, Digi
Connect WAN 3G, ConnectPort
WAN, PortServer TS H, Digi
TransPort WR21.

PART NUMBER:
76000752

Input Specifications:

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz

- Rated input current: 0.4A (rms) max. for 115VAC, 0.2 A (rms) max. for 230VAC
- Max. in-rush current: 25A MAX. @ 115VAC, 50A max. @ 230VAC at 25° C ambient cold start.
- Input Plug Type: NEMA 5-15P (NA)
- Leakage current: 1.0 mA max @230Vac.

Output Specifications:

- Output Voltage: 12VDC
- Load current: 1.0A
- Output Plug: 9.5 x 5.5 x 2.1mm locking barrel plug
- Max. output power: 12 watts continuous

Environment:

- Operating Temperature: -35° C to 74° C
- Storage Temperature: -35° C to 85° C

Dimensions:

- Size: 93 x 57 x 34mm
- Cord Length: 10ft

Approvals:

- Certifications: UL, cUL, CE