



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





AC Power Supply - 12VDC, extended temp. IEC320 to 2.1mm locking barrel plug. Compatibility: Digi TransPort WR41, Digi TransPort WR21, Digi Connect WAN 3G

PART NUMBER:

76000788



Specs:

Input Specifications:

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz
- Rated input current: 0.4A (rms) max. for 115VAC, 0.2 A (rms) max. for 230VAC
- Max. in-rush current: 25A MAX. @ 115VAC, 50A max. @ 230VAC at 25° C ambient cold start.
- Input Plug Type: IEC320 C14
- Leakage current: 1.0 mA max @230Vac.

Output Specifications:

- Output Voltage: 12VDC

- Load current: 1.0A
- Output Plug: Shogyo MP-121AR (9.5 x 5.5 x 2.1mm) locking barrel plug
- Max. output power: 12 watts continuous

Environment:

- Operating Temperature: -35° C to 74° C
- Storage Temperature: -35° C to 85° C

Dimensions:

- Size: 93 x 57 x 34mm
- Cord Length: 4ft

Approvals:

- Certifications: UL, cUL, CE