



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AC Power Supply - 12VDC.
Universal plugs (US, EU, UK, AU) to
2.1mm locking barrel plug.
Compatibility: Digi TransPort
WR41 (locking power cord
models), Digi TransPort WR44
(locking power cord models), Digi
TransPort WR21.

PART NUMBERS



North America: **76000823**

International: **76000823**

[See larger view](#)

Input Specifications:

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz
- Rated input current: < 0.6 A RMS MAX
- Max. in-rush current: 30A max. @ cold start 120VAC, 60A max. @ cold start 230VAC
- Input Plug Type: Includes four input connectors: NA, EU, UK, and AU. Leakage current: < 0.3 mA @ 240 VAC

Output Specifications:

- Output Voltage: 12VDC
- Load current: 1.5A
- Output Plug: 9.5 x 5.5 x 2.1mm locking barrel plug
- Max. output power: 18W max.

Environment:

- Operating Temperature: 0°C TO 40° C
- Storage Temperature: -40°C TO 80° C

Dimensions:

- Size: 84 x 56 x 37.9mm
- Cord Length: 6ft

Approvals:

- Certifications: UL, cUL, CE, RoHS

Contact a Digi expert and get started today!

[CONTACT US](#)