



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**AC Power Supply - 12VDC.
Universal plugs (US, EU, UK, AU) to
EIAJ non-locking barrel plug.
Compatibility: WR41 (12V non-
locking power cord models), WR44
(non-locking power cord models),
DR64.**

Product #: 76000824

Input Specifications:

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47Hz to 63Hz
- Rated input current: 0.6A RMS MAX
- Max. in-rush current: 30A typical @ 115Vac, 60A typical @ 230Vac
- Input Plug Type: Includes four input connectors: NA, EU, UK, and AU.
- Leakage current: < 0.3 mA @ 240 VAC

Output Specifications:

- Output Voltage: 12VDC
- Load current: 1.5A
- Output Plug: 5.5 x 3.3 x 1.0 x 9.5mm (EIAJ-04) barrel plug
- Max. output power: 18 watts

Environment:

- Operating Temperature: 0°C TO 40° C
- Storage Temperature: -10°C TO 80°C

Dimensions:

- Size: 74 x 43.5 x 34 mm
- Cord Length: 6ft

Approvals:

- Certifications: UL, cUL, CE, RoHS