



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**AC Power Supply -  
12VDC. North America  
plug to 2.1mm locking  
barrel plug.**

**Compatibility: Digi  
TransPort WR41  
(locking power cord  
models), Digi TransPort  
WR44 (locking power  
cord models), Digi  
TransPort WR21.**



PART NUMBER:

76000957

**Input Specifications:**

- Rated input voltage rating: 100VAC to 240VAC
- Input frequency: 47 Hz to 63 Hz
- Rated input current: < 0.6 A RMS MAX
- Max. in-rush current: 30A max. @ cold start 120VAC, 60A max. @ cold start 230VAC

- Input Plug Type: North America.
- Leakage current: < 0.3 mA @ 240 VAC

**Output Specifications:**

- Output Voltage: 12VDC
- Load current: 1.5A
- Output Plug: 9.5 x 5.5 x 2.1mm locking barrel plug
- Max. output power: 18W max.

**Environment:**

- Operating Temperature: 0°C TO 40° C
- Storage Temperature: -40°C TO 80° C

**Dimensions:**

- Size: 84 x 56 x 37.9mm
- Cord Length: 6ft

**Approvals:**

- Certifications: UL, cUL, CE, RoHS