imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Model 760KIT

pH Meter with Probe

Data Sheet

Intelligent pH Meter w/ Probe

Model 760KIT

- pH meter with mV measurement
- RS-232 PC Interface
- Plug and Play function
- pH Probe

pH Probe

Applications	High quality, Professional,	
	laboratory & field usage.	
Measuring Range	0 to 14 pH	
Measuring Temp	0 to 100°c (32° to 100° F)	
Electrode Structure	Combination type.	
Zero Potential for	71 pH	
pH Value		
Body Material	Ероху	
Connector	BNC	
Mechanical	With protection bottle on the	
Protection	electrode head	
Dimensions	Body Length - 120 mm	
	Body Dia - 9.5 mm	
	Cable Length - 750 mm	



pH meter

Measurement	Range	Resolution	Accuracy
рН	0 to 14 pH	0.01 pH	± (0.02 PH + 2 dgt)
mV	0 to 1999 mV	1 mV	± (0.5% + 2 dgt)

* pH accuracy is based on calibrated meter only.

* Specification tests under the environment RF Field Strength less than V/M & frequency less than 30 MHz only.