



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Datasheet for 76650-0030

General Information

| | |
|---------------------------|--|
| Part Number: | 76650-0030 |
| Manufacturer: | Molex / Waldom |
| Title: | Solderless Terminals |
| Description: | Assorted Non-Insulated and PVC Insulated Quick Disconnect, Ring, Spade and Butt Splice Terminals. Nylon Insulated Closed-End Terminals, with Universal Crimping Tool |
| Product Family: | Solderless Terminals |
| Certificates: | (Molex Parts within this kit) - EU RoHS Compliant, and UL |
| Country of Origin: | Kit assembled in U.S.A. |

Specifications

Design

| | |
|------------------------|--|
| Configuration: | Wire-to-Wire, Wire-to-Board / Solderless Terminals |
| Size(s): | .250", # 6 and # 10 |
| Insulation: | PVC (except Nylon Closed-end) and non-insulated |
| Current Rating: | Per (Proper) Wire Specification |
| Voltage: | 600 Volts |
| Wire size: | (22-18) and (16-14) |

Product Highlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Spades have the open tongue end used for rapid insertion on the mounting screw. The spade is usually used on free standing studs.

Butt Splices allow two stripped wires to be inserted into each end and "butt" in the center, with the crimp securing both wires together.

Features and Benefits

Applications

Datasheet for 76650-0030

- Terminals employ the full barrel length that eliminates costly and time consuming location when crimping
 - Finest quality electrolytic copper
 - One-piece design, butted seam
 - The Spade's open tongue end is for rapid insertion on the mounting screw / stud
 - The basic Ring Tongue type is the safest and most reliable because it cannot be disconnected unless the screw is completely removed.
 - Block Spades are designed for use in terminal blocks
- MRO (Maintenance Repair and Operations)
 - Consumer applications
 - Power applications
 - Motor applications
 - Powertrains
 - Transportation
 - Construction / Mining
 - Energy / Power
 - Production Equipment
 - Instrumentation
 - Environmental Equipment and Controls
 - Blower Motors

Datasheet for 76650-0030

Bill of Materials for Part No. 76650-0030

| Molex Part No. | Country of Origin | Description | Quantity in Kit |
|-----------------------|--------------------------|---|------------------------|
| 19016-0111 | USA | Non-insulated .250" Female Quick Disconnects, 16-14 AWG | 20 |
| 19017-0037 | USA | Insulated .250" Female Quick Disconnects, 16-14 AWG | 20 |
| 19022-0018 | USA | Non-insulated .250" Male Quick Disconnects, 16-14 AWG | 20 |
| 19023-0012 | USA | Insulated .250" Male Quick Disconnects, 16-14 AWG | 20 |
| 19044-0032 | USA | Non-insulated #6 Ring Tongue Terminals, 22-18 AWG | 20 |
| 19044-0068 | USA | Non-insulated #10 Ring Tongue Terminals, 22-18 AWG | 20 |
| 19044-0072 | USA | Non-insulated #6 Ring Tongue Terminals, 16-14 AWG | 20 |
| 19044-0152 | USA | Non-insulated #10 Ring Tongue Terminals, 16-14 AWG | 20 |
| 19054-0035 | USA | Insulated #6 Ring Tongue Terminals, 22-18 AWG | 20 |
| 19054-0039 | USA | Insulated #10 Ring Tongue Terminals, 22-18 AWG | 20 |
| 19054-0081 | USA | Insulated #6 Ring Tongue Terminals, 16-14 AWG | 20 |
| 19054-0113 | USA | Insulated #10 Ring Tongue Terminals, 16-14 AWG | 20 |
| 19119-0004 | USA | Insulated #6 Flanged Block Spade Terminals, 22-18 AWG | 20 |
| 19118-0021 | USA | Non-insulated #6 Flanged Block Spade Terminals, 22-18 AWG | 20 |
| 19128-0021 | USA | Non-insulated #6 Block Spade Terminals, 16-14 AWG | 20 |
| 19130-0044 | USA | Insulated #6 Block Spade Terminals, 16-14 AWG | 20 |
| 19130-0046 | USA | Insulated #10 Block Spade Terminals, 16-14 AWG | 20 |
| 19146-0037 | USA | Non-insulated #10 Block Spade Terminals, 16-14 AWG | 20 |
| 19154-0004 | USA | Insulated Butt Splice Connectors, 22-18 AWG | 20 |
| 19154-0015 | USA | Insulated Butt Splice Connectors, 16-14 AWG | 20 |
| 19160-0002 | USA | Insulated Nylon Closed-end Connectors, 16-14 AWG | 20 |
| 19189-0002 | USA | Non-insulated Butt Splice Connectors, 22-18 AWG | 20 |
| 19189-0008 | USA | Non-insulated Butt Splice Connectors, 16-14 AWG | 20 |
| CT-4071-1R^ | Taiwan | Universal Hand Crimping Tool, 22-10 AWG | 1 |

^ =Tool Provided by Waldom

Datasheet for 76650-0030

Recommended Molex Tool(s) for Part No. 76650-0030*

| Molex Part No. | Country of Origin | Description |
|-----------------------|--------------------------|----------------------------|
| 64001-0100 * | USA | Hand Crimp Tool (RHT-1990) |
| 64001-0200 * | USA | Hand Crimp Tool (RHT-1991) |
| 64001-0300 * | USA | Hand Crimp Tool (RHT-1993) |
| 64001-1400 * | USA | Hand Crimp Tool (RHT-2100) |
| 64001-2000 * | USA | Hand Crimp Tool (RHT-5758) |
| 64003-0100 * | USA | Hand Crimp Tool (RHT-1992) |

*Tool(s) not included in kit. Tool(s) ordered separately.