

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0039

General Information

Part Number: 76650-0039 Manufacturer: Molex / Waldom

Title: Solderless Terminal Kit

Description: Assorted PVC Insulated Quick Disconnect, Ring, Spade and Butt Splice Terminals.

Nylon Insulated Closed-End Solderless Terminals, With Universal Crimping Tool

Product Family: Solderless Terminals

Certificates: (Molex Parts within this kit) - EU RoHS Compliant, UL and CSA

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: (Wire-to-Wire) and (Wire-to-Board) / Solderless Terminals

.250", # 6, # 10, 1/4" and 3/8" Size(s):

Insulation: PVC and Nylon

Features and Benefits

Current Rating: Per (Proper) Wire Specification Voltage: Per (Proper) Wire Specification

Wire size: (22-18), (22-14), (16-14) and (12-10)

Product Highlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Spades have the open tongue end used for rapid insertion on the mounting screw.

The spade is usually used on free standing studs.

Closed-end connectors are used in a variety of situations to "pigtail" or tie together 2 or more wires.

Butt Splices allow two stripped wires to be inserted into each end and "butt" in the

Applications

center, with the crimp securing both wires together.

1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0039

- Color-coded insulator allows easy identification of terminal size and wire gauge.
- A wire stop stamped into the crimp barrel prevents insertion of over-stripped wires.
- Terminal's funnel entrance is designed for increased crimping rates by speeding wire delivery into the crimp section and eliminating wire strand fold back.
- The spade's open tongue end is for rapid insertion on the mounting screw / stud
- The basic ring tongue type is the safest and most reliable because it cannot be disconnected unless the screw is completely removed.

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications
- Powertrains
- Transportation
- · Construction / Mining
- · Energy / Power
- Production Equipment
- Instrumentation
- Environmental Equipment and Controls
- · Blower Motors



Datasheet for 76650-0039

Bill of Materials for Part No. 76650-0039			
Molex Part No.	Country of Origin	Description	Quantity in Kit
19017-0037	USA	Insulated .250" Female Quick Disconnects, 16-14 AWG	10
19023-0012	USA	Insulated .250" Male Quick Disconnects, 16-14 AWG	10
19054-0035	USA	Insulated #6 Ring Tongue Terminals, 22-18 AWG	10
19054-0039	USA	Insulated #10 Ring Tongue Terminals, 22-18 AWG	10
19054-0081	USA	Insulated #6 Ring Tongue Terminals, 16-14 AWG	10
19054-0113	USA	Insulated #10 Ring Tongue Terminals, 16-14 AWG	10
19070-0123	USA	Insulated #10 Ring Tongue Terminals, 12-10 AWG	10
19119-0004	USA	Insulated #6 Flanged Block Spade Terminals, 22-18 AWG	10
19130-0044	USA	Insulated #6 Block Spade Terminals, 16-14 AWG	10
19130-0046	USA	Insulated #10 Block Spade Terminals, 16-14 AWG	10
19154-0004	USA	Insulated Butt Splice Connectors, 22-18 AWG	10
19160-0009	USA	Insulated Nylon Closed-end Connectors, 22-14 AWG	10
CT-4071-1R^	Taiwan	Universal Hand Crimping Tool, 22-10 AWG	1
3. 707 1 111	Taiwaii	^ =Tool Provided by Waldom	1 '

Recommended Molex Tool(s) for Part No. 76650-0039*

Country

Molex Part No.	of Origin	Description
<u>64001-0100</u> *	USA	Hand Crimp Tool (RHT-1990)
64001-0200 *	USA	Hand Crimp Tool (RHT-1991)
<u>64001-0300</u> *	USA	Hand Crimp Tool (RHT-1993)
<u>64001-0600</u> *	USA	Hand Crimp Tool (RHT-7000)
<u>64001-1400</u> *	USA	Hand Crimp Tool (RHT-2100)
<u>64001-1500</u> *	USA	Hand Crimp Tool (RHT-2200)
<u>64001-2000</u> *	USA	Hand Crimp Tool (RHT-5758)
<u>64001-4700</u> *	USA	Hand Crimp Tool (RHT-2761-CC)

^{*}Tool(s) not included in kit. Tool(s) ordered separately.