



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Datasheet for 76650-0116

General Information

| | |
|---------------------------|---|
| Part Number: | 76650-0116 |
| Manufacturer: | Molex / Waldom |
| Title: | Mini-Lock Connector Kit |
| Description: | Fully Shrouded Positive Lock Right Angle Header and Receptacle |
| Product Family: | Mini-Lock™ |
| Certificates: | (Molex parts within this kit) EU and China RoHS Compliant, UL and CSA |
| Country of Origin: | Kit assembled in U.S.A. |

Specifications

Design

| | |
|------------------------|-----------------------|
| Configuration: | Wire-to-Board |
| Pitch: | 2.50mm (.098") |
| Connector Type: | Receptacle and Header |

Mounting

| | |
|------------------------|------------------|
| Orientation: | Right Angle |
| Circuit Sizes: | 2, 3, 4, 5 and 6 |
| Current Rating: | 3 Amps |
| Voltage: | 250 Volts |
| Wire size: | 28-22 AWG |

Product Highlights

Mini-Lock is a versatile wire-to-board system from Molex for a broad range of 2.50mm (.098") pitch industry standard applications. The kit includes Right Angle headers. Mini-Lock is fully shrouded to protect contacts, and includes high guide walls to facilitate mating.

Features and Benefits

- Four point contact design for good electrical reliability
- Thumb-latch locking feature for easy mating and unmating
- High guide walls to facilitate mating
- Fully shrouded headers to protect pins
- Pull tabs to assist in unmating

Applications

- White goods
- Vending machines
- Automotive
- PDAs
- TVs

Datasheet for 76650-0116

Bill of Materials for Part No. 76650-0116

| Molex Part No. | Country of Origin | Description | Quantity in Kit |
|----------------|-------------------|--|-----------------|
| 50351-8100-C | Japan | Mini-Lock™ Female Crimp Terminals 28-22 AWG | 100 |
| 51103-0200 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Receptacles 2 Circuits | 5 |
| 51103-0300 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Receptacles 3 Circuits | 5 |
| 51103-0400 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Receptacles 4 Circuits | 5 |
| 51103-0500 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Receptacles 5 Circuits | 5 |
| 51103-0600 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Receptacles 6 Circuits | 5 |
| 53426-0210 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Right Angle Headers 2 Circuits | 5 |
| 53426-0310 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Right Angle Headers 3 Circuits | 5 |
| 53426-0410 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Right Angle Headers 4 Circuits | 5 |
| 53426-0510 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Right Angle Headers 5 Circuits | 5 |
| 53426-0610 | Japan | 2.50mm (.098") Pitch Mini-Lock™ Right Angle Headers 6 Circuits | 5 |

Recommended Molex Tool(s) for Part No. 76650-0116*

| Molex Part No. | Country of Origin | Description |
|----------------|-------------------|-----------------|
| 63811-8100 * | Sweden | Hand Crimp Tool |
| 57309-6000 * | Japan | Extraction Tool |

*Tool(s) not included in kit. Tool(s) ordered separately.