

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0150

General Information

Part Number: 76650-0150

Manufacturer: Molex / Waldom

Title: Micro Miniature Application Kit

Includes CLIK-Mate, PanelMate, Sherlock, Pico-Spox and MicroClasp Prodcut Families. Pitches range: 1.25mm (.049") - 2.00mm (.079"). Positive and Friction

Description: Lock.

Product Family: CLIK-Mate[™], PanelMate[™], Sherlock[™], Pico-Spox[™], and MicroClasp[™]

Certificates: (Molex Parts within this kit) - EU RoHS Compliant

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: Wire-to-Board and Wire-to-Wire

Pitch: 1.25mm (.049"), 1.50mm (.059"), and 2.00mm (.079")

Connector Type: Receptacles, Plugs and Headers

Mounting

Orientation: Vertical and Right Angle
Circuit Sizes: 2, 3, 4, 6, 8, 9, 12 and 14
Current Rating: 1 Amp, 2 Amps, and 3 Amps

Voltage: 30, 50, 125, 250 Volts

Wire size: (32-30), (30-28), (30-24), & (26-22) AWG

Product Highlights

Molex's PanelMate[™] series is an ultra low-profile connector system designed for tight packaging applications. - Molex's new CLIK-Mate[™] connectors provide dual positive locks and a superior audible "click" to help ensure connectors are fully mated. - The Sherlock[™] system utilizes Molex's proven 50212 terminal, along with a positive lock housing. - Molex's new MicroClasp[™] system provides space savings and easy mating/unmating, plus, includes a unique inner positive lock that provides latch protection, secure retention and an audible mating "click". - Pico-Spox[™] provides Anti-fishhooking box design protects contact area



Datasheet for 76650-0150

Features and Benefits

- Tuning fork style contact design Secure contact, and avoids terminal stubbing
- Flat area for pick-and-place Easy automatic board placement
- Audible "click", low insertion force and secure mating / Inner positive lock Latch protection, secure mating, audible "click"
- Box-style contact Protects contact area / Two-point contact design Secure electrical contact, High current capable
- Polarizing features Ensures proper mating / Reinforced metal solder tabs Secure PCB

Applications

- · Appliances White Goods
- Automotive
- Home Applications LCD/PDP TVs Consumer
- Computer Data Communication equipment Vending and Gaming
- Industrial and Business Equipment Office machines Medical
- Any application requiring superior mating assurance

Bill of Materials for Part No. 76650-0150

Molex Part No.	Country of Origin	Description	Quantity in Kit
50641-8141	Japan	PanelMate™ Female Terminal 30-28 AWG	25
50753-8141	Japan	PanelMate™ Female Terminal 32-30 AWG	25
51146-0200	Japan	1.25mm (.049") Pitch PanelMate™, 2 Circuit Ultra Low-Profile Receptacle	2
51146-0600	Japan	1.25mm (.049") Pitch PanelMate™, 6 Circuit Ultra Low-Profile Receptacle	2
51146-0900	Japan	1.25mm (.049") Pitch PanelMate™, 9 Circuit Ultra Low-Profile Receptacle	2
53780-0270-P	Japan	1.25mm (.049") Pitch PanelMate™, 2 Circuit Right Angle Header	2
53780-0670-P	Japan	1.25mm (.049") Pitch PanelMate™, 6 Circuit Right Angle Header	2
53780-0970-P	Japan	1.25mm (.049") Pitch PanelMate™, 9 Circuit Right Angle Header	2
502438-0100	Japan	CLIK-Mate™ Male Crimp Terminal 26-22 AWG Loose	50
502439-0400	Japan	2.0mm (.079") Pitch CLIK-Mate™, 4 Circuit Plug Housing	2
502439-0600	Japan	2.0mm (.079") Pitch CLIK-Mate™, 6 Circuit Plug Housing	2
502439-0800	Japan	2.0mm (.079") Pitch CLIK-Mate™, 8 Circuit Plug Housing	2
502443-0470	Japan	2.0mm (.079") Pitch CLIK-Mate™, 4 Circuit Receptacle Vertical SMT	2
502443-0670	Japan	2.0mm (.079") Pitch CLIK-Mate™, 6 Circuit Receptacle Vertical SMT	2
502443-0870	Japan	2.0mm (.079") Pitch CLIK-Mate™, 8 Circuit Receptacle Vertical SMT	2
502494-0470	Japan	2.0mm (.079") Pitch CLIK-Mate™, 4 Circuit Receptacle Right Angle SMT	2



Datasheet for 76650-0150

1	1		
502494-0670	Japan	2.0mm (.079") Pitch CLIK-Mate™, 6 Circuit Receptacle Right Angle SMT	2
502494-0870	Japan	2.0mm (.079") Pitch CLIK-Mate™, 8 Circuit Receptacle Right Angle SMT	2
87421-0000-C	SINGAPORE	Pico-Spox™ Female Crimp Terminal, Tin (Sn), 24-30 AWG	100
87437-0343-P	SINGAPORE	1.50mm (.059") Pitch Pico-Spox™, 3 Circuit, Vert., SMT, Header	2
87437-0443-P	SINGAPORE		2
87437-0643-P	SINGAPORE		2
87438-0343-P	SINGAPORE		2
87438-0443-P	SINGAPORE	1.50mm (.059") Pitch Pico-Spox™, 4 Circuit, R/A, SMT, Header	2
87438-0643-P	SINGAPORE	1.50mm (.059") Pitch Pico-Spox™, 6 Circuit, R/A, SMT, Header	2
87439-0300	SINGAPORE		2
87439-0400	SINGAPORE		2
87439-0600	SINGAPORE	1.50mm (.059") Pitch Pico-Spox™, 6 Circuit, Receptacle Housing	2
50212-8100	Japan	Female Loose Crimp Terminal 30-24 AWG	100
35507-0300	KOREA	2.0mm Pitch Sherlock™, 3 Circuit Receptacle Housing	2
35507-0400	KOREA	2.0mm Pitch Sherlock™, 4 Circuit Receptacle Housing	2
35507-0600	KOREA	2.0mm Pitch Sherlock™, 6 Circuit Receptacle Housing	2
35362-0350	KOREA	2.0mm Pitch Sherlock™, 3 Circuit Vertical Header	2
35362-0450	KOREA	2.0mm Pitch Sherlock™, 4 Circuit Vertical Header	2
35362-0650	KOREA	2.0mm Pitch Sherlock™, 6 Circuit Vertical Header	2
35363-0360	KOREA	2.0mm Pitch Sherlock™, 3 Circuit Right Angle Header	2
35363-0460	KOREA	2.0mm Pitch Sherlock™, 4 Circuit Right Angle Header	2
35363-0660	KOREA	2.0mm Pitch Sherlock™, 6 Circuit Right Angle Header	2
56134-9100	Japan	MicroClasp™ Female Terminal 26-22 AWG	25
51353-0800	Japan	2.00mm (.079") Pitch MicroClasp™ 8 Circuit Receptacle Dual Row	2
51353-1200	Japan	2.00mm (.079") Pitch MicroClasp™ 12 Circuit Receptacle Dual Row	2
51353-1400	Japan	2.00mm (.079") Pitch MicroClasp™ 14 Circuit Receptacle Dual Row	2
55959-0830	Japan	2.00mm (.079") Pitch MicroClasp™ 8 Circuit Right Angle Header Dual Row	2
55959-1230	Japan	2.00mm (.079") Pitch MicroClasp™ 12 Circuit Right Angle Header Dual Row	2

1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0150

		2.00mm (.079") Pitch MicroClasp™ 14 Circuit Right Angle	
55959-1430	Japan	Header Dual Row	2



Datasheet for 76650-0150

Recommended Molex Tool(s) for Part No. 76650-0150*

Molex Part No.	Country of Origin	Description
63811-7900 *	SWEDEN	Hand Crimp Tool , UL Approved - PanelMate™
57352-5000 *	USA	JAPAN Hand Crimp Tool - PanelMate™
57352-5100 *	JAPAN	JAPAN Hand Crimp Tool - PanelMate™
63819-2800 *	SWEDEN	Hand Crimp Tool - (22-26 AWG Terminals) CLIK-Mate™
11-03-0043 *	USA	Extraction Tool - CLIK-Mate™
63811-6400 *	GERMANY	Hand Crimp Tool - Pico-Spox™
63819-0500 *	SWEDEN	Hand Crimp Tool - Sherlock™ / Micro-Latch™
57105-6000 *	USA	Extraction Tool - Sherlock™ / Micro-Latch™
63811-6300 *	GERMANY	Hand Crimp Tool - MicroClasp™
57404-5300 *	JAPAN	JAPAN Hand Crimp Tool - MicroClasp™
57399-6000 *	JAPAN	JAPAN Extraction Tool - MicroClasp™

^{*}Tool(s) not included in kit. Tool(s) ordered separately.