



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Datasheet for 76650-0162

### General Information

<b>Part Number:</b>	76650-0162
<b>Manufacturer:</b>	Molex / Waldom
<b>Title:</b>	EXTreme Power Edge Connector Kit
<b>Description:</b>	End to End Stackable PCB, Through Hole and Press-Fit Connector, 40A 250V
<b>Product Family:</b>	EXTreme PowerEdge™
<b>Certificates:</b>	(Molex Parts within this kit) - EU RoHS Compliant, UL and CSA
<b>Country of Origin:</b>	Kit assembled in U.S.A.

### Specifications

#### Design

<b>Configuration:</b>	Wire-to-Wire and Board-to-Board
<b>Pitch:</b>	12.90mm (.508")
<b>Type:</b>	Through Hole and Press-Fit
<b>Sizes:</b>	4 and 6 Contact Versions
<b>Current Rating:</b>	40 Amps
<b>Voltage:</b>	250V

### Product Highlights

EXTreme PowerEdge connectors are designed for direct mating to a customer's 1.58mm (.062") thick, double-sided card edge PCB or bus bar tab. These PCB connectors are High Current, up to 40.0A per contact.

### Features and Benefits

- High current, up to 40.0A per contact
- Rated for current interruption
- Press-fit or solder tail terminations, compatible with standard PCB's or backplanes
- Available in 2 or 3 segments (2 contacts per segment)
- End-to-end stackable to mate with double-sided card edge lengths of up to 203.20mm (8.000")
- Compatible with competitive connector, drop-in replacement
- Isolated contacts on opposite side of connector assembly segments

### Applications

- Telecommunications Equipment: Networking Hubs, Switches, Routers
- High and Mid-Range Computing Equipment
- Un-interruptible Power Supplies (UPS)
- Cellular Communications Equipment: Base Stations
- DC-DC Converters

### Datasheet for 76650-0162

#### Bill of Materials for Part No. 76650-0162

Molex Part No.	Country of Origin	Description	Quantity in Kit
45719-0004	USA	12.90mm (.508") Pitch EXTreme PowerEdge™, 2 Segments, 4 Contacts, 2.36mm (.093") PCB	1
45719-0005	USA	12.90mm (.508") Pitch EXTreme PowerEdge™, 3 Segments, 6 Contacts, 2.36mm (.093") PCB	1
45719-0007	USA	12.90mm (.508") Pitch EXTreme PowerEdge™, 2 Segments, 4 Contacts, 1.57mm (.062") PCB	2
45719-0008	USA	12.90mm (.508") Pitch EXTreme PowerEdge™, 3 Segments, 6 Contacts, 1.57mm (.062") PCB	2
45714-0001	USA	12.90mm (.508") Pitch EXTreme PowerEdge™ Press-fit, 2 Segments, 4 Contacts	1
45714-0002	USA	12.90mm (.508") Pitch EXTreme PowerEdge™ Press-fit, 3 Segments, 6 Contacts	1

#### No Recommended Molex Tool for Part No. 76650-0162