



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## General Information

<b>Part Number:</b>	76650-0224
<b>Manufacturer:</b>	Molex / Waldom
<b>Title:</b>	MV-396 Power Connector Kit
<b>Description:</b>	Low Profile Pos Lock Interconnect Vertical Header and Receptacle, 7A 250V
<b>Product Family:</b>	MV-396™
<b>Certificates:</b>	(Molex Parts within this kit) - EU and China RoHS Compliant, UL and CSA
<b>Country of Origin:</b>	Kit assembled in U.S.A.

## Specifications

### Design

<b>Configuration:</b>	Wire-to-Board
<b>Pitch:</b>	3.96mm (.156")
<b>Connector Type:</b>	Receptacle and Header

### Mounting

<b>Orientation:</b>	Vertical
<b>Circuit Sizes:</b>	2, 3, 4, 5 and 6 circuits
<b>Current Rating:</b>	7 Amps
<b>Voltage:</b>	250 Volts
<b>Wire size:</b>	20-18 AWG

## Product Highlights

The MV-396 wire-to-board system is a robust interconnect solution for industry-standard 3.96mm (.156") pitch applications. The system offers a positive lock for secure mating retention, and a double cantilever terminal design with unique metal shroud that prevents contamination and provides high contact pressure. The system carries up to 7 amps and is offered in 2 to 15 circuit sizes. Both vertical and right angle headers provide low profiles and a partially shrouded design for space savings and secure latching.

### Features and Benefits

- Positive lock for secure mating retention
- Double cantilever terminal with metal shroud for protection and high contact pressure
- Polarization prevents mis-mating
- Low profile offers good space savings

### Applications

- Security and Alarms
- Comfort and Infotainment
- Vending and Gaming
- Business Machines
- Energy and Power
- Industrial Equipment

**[For additional Molex / Waldom Design and Solution kits please go to www.molexkits.com](http://www.molexkits.com)**

**Bill of Materials for Part No. 76650-0224**

Molex Part No.	Country of Origin	Description	Quantity in Kit
35922-8011-C	S. Korea	MV-396™ Female Terminals Phosphor Bronze 18-20 AWG	100
35977-0200	S. Korea	3.96mm (.156") MV-396™ Wire-to-Board connector Receptacle 2 circuit	5
35977-0300	S. Korea	3.96mm (.156") MV-396™ Wire-to-Board connector Receptacle 3 circuit	5
35977-0400	S. Korea	3.96mm (.156") MV-396™ Wire-to-Board connector Receptacle 4 circuit	5
35977-0500	S. Korea	3.96mm (.156") MV-396™ Wire-to-Board connector Receptacle 5 circuit	5
35977-0600	S. Korea	3.96mm (.156") MV-396™ Wire-to-Board connector Receptacle 6 circuit	5
35978-0210	S. Korea	3.96mm (.156") Pitch MV-396™ Header, Vertical, 2 Circuits	5
35978-0310	S. Korea	3.96mm (.156") Pitch MV-396™ Header, Vertical, 3 Circuits	5
35978-0410	S. Korea	3.96mm (.156") Pitch MV-396™ Header, Vertical, 4 Circuits	5
35978-0510	S. Korea	3.96mm (.156") Pitch MV-396™ Header, Vertical, 5 Circuits	5
35978-0610	S. Korea	3.96mm (.156") Pitch MV-396™ Header, Vertical, 6 Circuits	5

**No Recommended Molex Tool for Part No. 76650-0224**