



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



R3 Dissipative Rubber Worksurface Mat



Made in the United States of America

Meets ANSI/ESD S20.20 worksurface required limit (and recommendation of ANSI/ESD S4.1) tested per ANSI/ESD S4.1 and ESD TR53. Resistance to solvents, hot solder and soldering irons makes the R3 Dissipative Rubber Worksurface Mat a versatile static-safe worksurface. Electrical performance is accomplished by using a two-layer rubber combination of a static dissipative colored top with a conductive black bottom. Compatible with Continuous Workstation Monitors. Available in rolls and mat kits.



Mat Kits are laser engraved for branding and auditing purposes.

Grounding: This material must be properly grounded for optimum electrical performance. See [Grounding Cords](#).

Cleaning: For optimum electrical performance, surface must be cleaned regularly using a recommended ESD mat cleaner. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

Specifications and procedures subject to change without notice.

Properties	Typical Value	Test Method
Thickness*	0.063" (1.6 mm) ±0.005"	
Color*	Green/Black Light Blue/Black Gray/Black Dark Blue/Black	
Resistances		
Surface to Ground (Rtg)	1 x 10 ⁶ to < 1 x 10 ⁹ ohms	ANSI/ESD S4.1, ESD TR53
Surface to Surface (Rtt)	1 x 10 ⁶ to < 1 x 10 ⁹ ohms	ANSI/ESD S4.1, ESD TR53
Hardness	65 ± 5 Shore "A"	ASTM-D2240
Tolerance		
Mat Kit	Width +/- 0.250" Length +/- 1"	
Rolls	Width +/- 0.250" Length +/- 2"	

*Color, texture and thickness may vary between lots and mills.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to condition for at least 4 hours before cutting to size. Always using care, trim with a sharp knife or razor blade.

Table Mat Kit Item Numbers

Size	Light Blue	Gray	Green
24" x 48" (0.6 m x 1.2 m)	770074	770090	770085

Table Mat Kit Includes:

- 1 Table Mat, size as specified
- 1 [LPCGC151M](#) 15' (4.6 m) Ground Cord
- 2 [3049](#) Snap Kit

Roll Item Numbers

Size	Light Blue	Gray	Green	Dark Blue
2' x 50' (0.6 m x 15.2 m)	770070	770086	770081	770091
2.5' x 50' (0.8 m x 15.2 m)	770071	770087	770082	770092
3' x 50' (0.9 m x 15.2 m)	770072	770088	770083	770093
4' x 50' (1.2 m x 15.2 m)	770073	770089	770084	

Includes roll of matting material.

R3 DISSIPATIVE RUBBER WORKSURFACE MAT

926 JR Industrial Drive, Sanford, NC 27332
 WEB SITE: [StaticControl.com](#)
 PHONE (919) 718-0000

DRAWING NUMBER
R3 Series

DATE
January 2018

