mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PAC PAC-SLC5-SD15-V1-1M5



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



The pre-assembled PAC cable provide the electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following elements:

- PLC connection from the manufacturer.
- Multi-pole LIYY or LY YCY (shielded) cable with 0.14 mm² or 0.25 mm² cross-section.
- SubD or RSV connectors for the connection to the interface.

The cables are automatically tested for continuity and isolation in order to guarantee their special functionality for which they were developed.

General ordering data

Order No.	<u>7789009015</u>		
Туре	PAC-SLC5-SD15-V1-1M5		
Version	Pre-assembled cable, PAC, Cable LiYCY, 0.25 mm ²		
GTIN (EAN)	8430243956796		
Qty.	1 pc(s).		

PAC PAC-SLC5-SD15-V1-1M5

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

	0.40 5			
Net weight	242.5 g			
Temperatures				
Operating temperature	-10+50°C	Storage temperature	-10+60 °C	
General Data				
Connector PLC side	WEIDMUELLER BLZ 5.08/8/90 SN OR	Interface connector	SUB-D FEMALE 15P	
Number of poles, min.	15-pole	Outer diameter	8.7 ± 1 mm	
Cable	Cable LiYCY	Cable length	1.5 m	
Material	PVC	Wire cross-section	0.25 mm ²	
Electrical Data				
Rated voltage (text)	≤ 60 Vdc ≤ 25 Vac	Permissible current strength per path, max.	1 A	
Total current, max.	3 A	Resistance	≤ 80 mΩ/m	
High voltage test	1 KV/1s			
Classifications				
eClass 6.2	27-14-11-52	eClass 7.1	27-14-11-52	
Notes				
Notes	The figure shows a generic product on offer.			
Approvals				
Approvals				
	PG			
	ME25			