

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PAC PAC-GF30-RV24-V4-1M5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



The pre-assembled PAC cable provide the electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following elements:

- PLC connection from the manufacturer.
- Multi-pole LIYY or LY YCY (shielded) cable with 0.14 mm² or 0.25 mm² cross-section.
- SubD or RSV connectors for the connection to the interface.

The cables are automatically tested for continuity and isolation in order to guarantee their special functionality for which they were developed.

General ordering data

Туре	PAC-GF30-RV24-V4-1M5
Order No.	<u>7789064015</u>
Version	Pre-assembled cable, PAC, Cable LiYY, 0.25 mm ²
GTIN (EAN)	8430243958240
Qty.	1 pc(s).



PAC PAC-GF30-RV24-V4-1M5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions	and	weights

Length	1.5 m	Net weight	317 g	
Temperatures				
Operating temperature		Storage temperature		
General Data				
Connector PLC side	GEFANUC IC693ACC311 20P	Interface connector	WEIDMUELLER RSV 24P MALE	
Number of poles, min.	24-pole	Outer diameter	9.2 ± 1 mm	
Cable	Cable LiYY	Cable length	1.5 m	
Material	PVC	Wire cross-section	0.25 mm ²	
Electrical Data				
Rated voltage (text)		Permissible current strength per path,		
	≤ 250 Vdc ≤ 250 Vac	max.	1 A	
Total current, max.	3 A	Resistance	≤ 80 mΩ/m	
High voltage test	1 KV/1s			
Classifications				
eClass 6.2	27-14-11-52	eClass 7.1	27-14-11-52	
eciass 0.2	27-14-11-02	eciass /. I	Z1-14-11-0Z	
Annrovale				

Approvals

Approvals

