

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PAC PAC-MICR-SD15-V1-5M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



The pre-assembled PAC cable provide the electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following elements:

- PLC connection from the manufacturer.
- Multi-pole LIYY or LY YCY (shielded) cable with 0.14 mm² or 0.25 mm² cross-section.
- SubD or RSV connectors for the connection to the interface.

The cables are automatically tested for continuity and isolation in order to guarantee their special functionality for which they were developed.

General ordering data

Туре	PAC-MICR-SD15-V1-5M		
Order No.	<u>7789310050</u>		
Version	Pre-assembled cable, PAC, Cable LiYCY, 0.25 mm ²		
GTIN (EAN)	8430243969376		
Qty.	1 pc(s).		



PAC PAC-MICR-SD15-V1-5M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	664 g				
Net weight	004 g				
Temperatures					
Operating temperature	-10+50°C	Storage temperature	-10+60 °C		
Operating temperature	-10130 C	Storage temperature	-10100 C		
General Data					
Connector PLC side	SCHNEIDER TSX BLZ H01	Interface connector			
Connector r LC side	15P	interface connector	SUB-D FEMALE 15P		
Number of poles, min.	15-pole	Outer diameter	8.7 ± 1 mm		
Cable	Cable LiYCY	Cable length	5 m		
Material	PVC	Wire cross-section	0.25 mm ²		
Electrical Data					
Rated voltage (text)		Permissible current strength per path,			
	≤ 60 Vdc ≤ 25 Vac	max.	1 A		
Total current, max.	3 A	Resistance	≤ 80 mΩ/m		
High voltage test	1 KV/1s				
Classifications					
eClass 6.2	27-14-11-52	eClass 7.1	27-14-11-52		
	27-14-11-02	001400 7.1	27 17-11-02		
Approvals					
Approvals					
	(PC				