

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PAC PAC-RX3i-SD37-V3-5M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a crosssection of 0.14 mm² or 0.25 mm².
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

General ordering data

Туре	PAC-RX3i-SD37-V3-5M
Order No.	<u>7789798050</u>
Version	Pre-assembled cable, PAC, Cable LiYCY, 0.25 mm ²
GTIN (EAN)	4032248124695
Qty.	1 pc(s).



PAC PAC-RX3i-SD37-V3-5M

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights				
Net weight	1,418 g			
Temperatures				
Operating temperature	-10+50°C	Storage temperature	-10+60 °C	
General Data				
Connector PLC side	GEFANUC IC694TBS032 36P	Interface connector	SUB-D FEMALE 37P	
Number of poles, min.	37-pole	Outer diameter	12.2 ± 1 mm	
Cable	Cable LiYCY	Cable length	5 m	
Material	PVC	Wire cross-section	0.25 mm ²	
Electrical Data				
Rated voltage (text)	.00VI .05V	Permissible current strength per path,		
Total current, max.	≤ 60 Vdc ≤ 25 Vac 3 A	max. Resistance	1 A ≤ 80 mΩ/m	
High voltage test	1 KV/1s	nesistance	≥ 00 III\2/III	
Classifications	110710			
eClass 6.2	27-06-03-90	eClass 7.1	27-24-92-05	
Approvals	27 00 00 00	001466 7.1	2, 2, 62 66	
Approvals	P G			
	ME25			
ROHS	Conform			