mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PAC PAC-RX3i-SD37-V5-5M



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a crosssection of 0.14 mm² or 0.25 mm².
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

General ordering data

Туре	PAC-RX3i-SD37-V5-5M	
Order No.	<u>7789849050</u>	
Version	Pre-assembled cable, PAC, Cable LiYCY, 0.25 mm ²	
GTIN (EAN)	4032248124824	
Qty.	1 pc(s).	

PAC PAC-RX3i-SD37-V5-5M

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
1.418 a			
1,410 g			
-10+50°C	Storage temperature	-10+60 °C	
GEFANUC IC694TBS032 36P	Interface connector	SUB-D FEMALE 37P	
37-pole	Outer diameter	12.2 ± 1 mm	
Cable LiYCY	Cable length	5 m	
PVC	Wire cross-section	0.25 mm ²	
	Permissible current strength per path,		
		1 A	
	Resistance	≤ 80 mΩ/m	
I KV/ IS			
27-06-03-90	eClass 7.1	27-06-03-90	
PG			
ME25			
Conform			
	1,418 g -10+50°C GEFANUC IC694TBS032 36P 37-pole Cable LiYCY PVC ≤ 60 Vdc ≤ 25 Vac 3 A 1 KV/1s 27-06-03-90 27-06-03-90	1,418 g -10+50°C Storage temperature GEFANUC IC694TBS032 36P Interface connector 37-pole Outer diameter Cable LiYCY Cable length PVC Wire cross-section ≤ 60 Vdc ≤ 25 Vac max. 3 A 1 KV/1s 27-06-03-90 eClass 7.1	