



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Home
Embedded Software

Development Tools
J-Link ARM

Adapters
5V adapter
JTAG 14 pin adapter
DFPUs
Flash breakpoints

Flash download
Flash SDK
GDB Server
IDE integration
Interface description

J-Flash ARM
J-Link software
J-Mem
JTAG Isolator
Model comparison

Non-commercial-use
Performance comparison
RDI
SDK
J-Link ARM Pro

J-Link ARM Lite
J-Link Coldfire
J-Trace ARM
J-Trace for Cortex-M3

Production Tools

Evaluate our software!
Downloads

Distributors
Customers

Partners
Sales

Forum
About us

Head office Germany

Phone: +49-2103-2375-0
Fax: +49-2103-2375-200
E-mail: info@segger.com
www.segger.com

US office

Phone: +1-975-874-0299
Fax: +1-975-874-0699
E-mail: info@segger-us.com
www.segger-us.com



[Development Tools](#) [J-Link ARM](#) [Adapters](#) [JTAG 14 pin adapter](#)

JTAG 14 pin adapter

An adapter is available to use J-Link ARM with targets using this 14 pin 0.1" mating JTAG connector.

Pin Signal Pin no. on 20 pin JTAG

| | | |
|----|-------|-----|
| 1 | Vtref | 1 |
| 2 | GND | GND |
| 3 | nTRST | 3 |
| 4 | GND | GND |
| 5 | TDI | 5 |
| 6 | GND | GND |
| 7 | TMS | 7 |
| 8 | GND | GND |
| 9 | TCK | 9 |
| 10 | GND | GND |
| 11 | TDO | 13 |
| 12 | RESET | 15 |
| 13 | Vtref | 1 |
| 14 | GND | GND |



Mapping between the JTAG 14 pin adapter and 20 pin JTAG interface

[Pricing](#)

[Imprint](#) [Disclaimer](#) [Sitemap](#)

[back to top](#)

© 2009, www.segger.com, All rights reserved.