



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
G	14	U4	REVISED PER ECO-11-004917	11MAR11	RK HMR

Technical drawing of Style I wire splice. Dimensions: A MAX (total length), B MIN (width). Callout: BODY.

Technical drawing of a wire splice showing dimensions: .409 REF (height), .330 REF (width).

Technical drawing of Style III wire splice. Dimensions: A MAX (total length), B MIN (width), .390 MIN X .320 MIN OVALED (height of ovals), .440 MIN (width of ovals).

Technical drawing of a wire splice showing dimensions: .409 REF (height), .330 REF (width).

Technical drawing of Style I wire splice showing INSULATION.

STYLE I

Technical drawing of Style III wire splice showing INSULATION.

BODY INSULATION

STYLE III

8-321235-5	2.625	.860	NATURAL	CLEANED		LOOSE PC, BOX SPL	100	600	300
8-321235-1	2.625	.860	NATURAL	CLEANED	I	LOOSE PC, BOX	100	600	300
3-321235-0 <sup>2</sup>	2.625	1.151	BLACK	<sup>1</sup>	I	LOOSE PC	1000		
1-321235-4	2.438	.870	NATURAL	CLEANED	III	LOOSE PC	1000	600	300
1-321235-1	2.625	1.151	NATURAL	<sup>1</sup>		LOOSE PC	1000	600	300
1-321235-0	2.625	1.151	NATURAL	CLEANED	I	LOOSE PC	1000	600	300
321235	2.093	.860	NATURAL	CLEANED		LOOSE PC	1000	300	300
PART NO.	DIM 'A'	DIM 'B'	COLOR	FINISH	STYLE	PACKAGE TYPE	QTY		
								MAX VOLTAGE RATING	

<sup>1</sup> TIN PLATE PER ASTM B545  
<sup>2</sup> PRELIMINARY - NOT FOR PRODUCTION

WIRE SPLICE	SEE TABLE	INSULATION: PVC COLOR: SEE TABLE BODY: BRASS (ASTM B-19) .032 THK FINISH: SEE TABLE
DESCRIPTION	PART NO.	MATERIAL & FINISH

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	06OCT00
DIMENSIONS: INCHES		CHK	T. MICHELUTTI	06OCT00
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	T. MICHELUTTI	06OCT00
0 PLC ± -		PRODUCT SPEC		
1 PLC ± -		APPLICATION SPEC		
2 PLC ± -				
3 PLC ± .008		WEIGHT	-	
4 PLC ± -		SCALE	NTS	
ANGLES ± -		SHEET	1 of 1	
FINISH		REV	U4	
SEE TABLE		CUSTOMER DRAWING		
		SIZE	A2	
		CAGE CODE	00779	
		DRAWING NO	C-321235	
		RESTRICTED TO	-	

321235

B

A

1471-9 (3/11)