



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



插頭部件 (Plug Component)			頭部剥皮尺寸 (Plug strip dimension)			線材規格(Wire Spec.)	尾部剥皮尺寸 (Terminal roj & Strip)			尾部處理 (Terminal Component)		
顏色(Color)	零件描述(Component)	數量(Q'ty)	內剥(Strip)	外剥(Roj)	顏色(Color)	SJT 12AWG/3C  105°C 黑色(Black)  線長: (Length) 1193.8 <sup>+50.8</sup> <sub>-12.7</sub>	外剥(Roj)	內剥(Strip)	顏色(Color)	顏色(Color)	零件描述(Component)	數量(Q'ty)
35P黑色	FM-320 (20A 250V-) (IEC 320 C20)	1	5 <sup>+1</sup> <sub>-0</sub>	20±1	黑/Black(L)		20±1	5 <sup>+1</sup> <sub>-0</sub>	黑/Black(L)	35P黑色	FM-319 (20A 250V-) (IEC 320 C19)	1
90A±2A Black 鍍鎳 (Nickel-Plated)	2.0A6.0電腦電源線端子 (Computer power cord terminal)	1	5 <sup>+1</sup> <sub>-0</sub>	20±1	白/White(N)		20±1	5 <sup>+1</sup> <sub>-0</sub>	白/White(N)	90A±2A Black 鍍鎳 (Nickel-Plated)	母插端子 (Receptacle Terminals)	3
鍍鎳 (Nickel-Plated)	2.0A5.0電腦電源線端子 (Computer power cord terminals)	2	5 <sup>+1</sup> <sub>-0</sub>	20±1	綠/Green(E)		20±1	5 <sup>+1</sup> <sub>-0</sub>	綠/Green(E)	黑色(Black)	FM-319兩件式內模 (FM-319 Inner Body)	1
黑色(Black)	FM-320兩件式內模 (FM-320 Inner Body)	1										




插頭端面圖  
(Dimensions of Plug Face)


Insulation Thickness 0.76 mm  
Overall Diameter 4.00±0.15 mm

Copper Conductor  
65/0.254±0.004 mm  
Resistance 5.58  
(20°C (Max). ohms/km)


Jacket Thickness 1.14 mm  
Overall Diameter 11.0±0.20 mm



線材截面圖  
(Wire Cross-Section)



A-CI 扎線圖示 (A-CI Hank Detail)



插頭端面圖  
(Dimensions of Plug Face)

包裝方式(Packing)	
扎線方式 (Bulk Pack)	依繞線圖示繞線 See Hank Detail(A-CI)
紙箱尺寸 (Carton Size)	480 X 320 X 250
包裝數量 (Packing Q'ty)	PCS
標籤 (Label)	UL Detachable Label
正側唛頭 (Carton Print)	依客戶要求印刷 (See Purchase Order)
電線印字內容 Wire Printed	使用充實線材 四印字 (Un-Filler, Gravure)
V E922763 (UL) SJT 12AWG(3.31mm²)×3C VW-I 105°C 300V /FT c(UL) SJT 12AWG(3.31mm²)×3C FT2 105°C 300V -LF- (UL) SJT 12AWG(3.31mm²)×3C VW-I 105°C 300V E77975 WONDERFUL-D CSA SJT 12AWG(3.31mm²)×3C FT2 105°C 300V LL43774 -F- -LF-	紙箱唛頭標碼 Shipping Mark
	◊ CnC ◊

SIZE :	A4
UNIT :	mm
SCALE :	1:1
PROJ. :	

SIGNATURE	NAME	DATE		
APPROVED				
M.F.G. CHECKED			2012/04/19	新版發行
Q.A. CHECKED			00/0419	楊承正
DRAWN	楊承正	2012/04/19	REV DATE	DESCRIPTION
CUSTOMER			PART No.	800-12-32D-BL-0004F
			DWG No.	
<b>CnC Tech. LLC</b> Industrial Cable and Connector Technology				