



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us





Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




插頭部件 (Plug Component)			頭部剥皮尺寸 (Dimensions)			線材規格 (Wire Styles)	尾部剥皮尺寸 (Dimensions)			端子規格 (Terminal Style)	
顏色(Color)	零件描述(Component)	Qty.	內剥(Stripped)	外剥(ROJ)	顏色(Color)	SJT 16AWGx3C 105°C 黑色 (Black) Length : 2000±50 (79"±2")	外剥(ROJ)	內剥(Stripped)	顏色(Color)	規格描述(Instruction)	端子編號(Style No.)
35P 黑色 (Black)	FM-302L (IEC 60320, C13)	1	6 <sup>+1</sup> <sub>-0</sub>	18 ± 2	黑/Black(L)		50.8±5	6.35±3	黑/Black(L)	絕緣依尺寸剥除,留膠於線上 (Strip and Retain Outside Insulated)	
銅本色 (Brass-Natural)	2.0*4.0 方管端子(GEM 98752A-0) (2.0*4.0 Receptacle Terminal)	3	6 <sup>+1</sup> <sub>-0</sub>	18 ± 2	白/White(N)		50.8±5	6.35±3	白/White(N)	絕緣依尺寸剥除,留膠於線上 (Strip and Retain Outside Insulated)	
米白色 (Off-White)	GA005-5 品字母插兩件式內模 (Computer 2x4 Serial Housing)	1	6 <sup>+1</sup> <sub>-0</sub>	18 ± 2	綠/Green(E)	50.8±5	6.35±3	綠/Green(E)	絕緣依尺寸剥除,留膠於線上 (Strip and Retain Outside Insulated)		



REV	DATE	REVISE CONTENT
A	08/29-2012	The first edition is issued and drawing.
F		

- NOTE:**
- Hi-Pot Test : 1500V/1Sec ; <0.5mA.
  - Insulation Resistance Test : DC 500/min>100 meg-ohm.
  - Continuity & Polarization Test : No short circuit, break circuit, displacement.
  - Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
  - Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
  - All material according to Non-toxic standard.(Material must be RoHS compliant.)
  - "FMC" logo maybe present on C13.

線材印字 (Wire Printed)	充實, 油墨印字 (Un-Fillers, Printing Ink)			<b>CnC Tech, LLC</b> Industrial Cable and Connector Technology				
包裝方式 (Packing)		DRAWN						CUSTOMER 
Tied Hank	See Hank Detail	Chu8.		P/N No.		800-1603-2-SJT0-BL-00200		
Carton Size	480 x 320 x 250	DATE		MATERIAL		PVC	UNIT	mm
Pack Number	100pcs/ <small>UL Laster Labels</small>	08/29-2012		Customer Approval				
Carton Print	See Purchase Order	TYPE		IEC 60320, C13 RA to ROJ(S&R) Power Supply Cord				
DRAWING NO.	098MM981	REV	A					

業務校閱：  
品質校閱：