



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



插頭部件 (Plug Component)			頭部包皮尺寸 (Plug strip dimension)			線材規格(Wire Spec.)	尾部包皮尺寸 (Terminal roj & Strip)			尾部處理 (Terminal Component)		
顏色(Color)	零件描述(Component)	數量(Q'ty)	內剝(Strip)	外剝(Roj)	顏色(Color)		外剝(Roj)	內剝(Strip)	顏色(Color)	顏色(Color)	零件描述(Component)	數量(Q'ty)
35P白色 90A+2A White	ME-301 (10A 125V-) (NEMA 5-15P)	1	5 ⁺¹ ₋₀	23±1	黑/Black(L)	SJT 18AWG/3C 105°C 白色(White) 線長: (Length) 3048 ^{+50.8} _{-12.7}	16±1	5 ⁺¹ ₋₀	黑/Black(L)	35P白色 90A+2A White	ME-302 (10A 125V-) (IEC 320 C-13)	1
鍍鎳 Nickel-Plated	Ø4.75 圓管端子 (Earth Pin Terminal)	1	5 ⁺¹ ₋₀	23±1	白/White(N)		16±1	5 ⁺¹ ₋₀	白/White(N)	銅本色 (Copper)	電腦電源線端子 GEM-987458S-0 Computer power cord terminals	3
鍍鎳 Nickel-Plated	6.3*1.5 單片圓頭端子 (Solid Blades)	2	5 ⁺¹ ₋₀	23±1	綠/Green(E)		16±1	5 ⁺¹ ₋₀	綠/Green(E)	白色(White)	ME-302兩件式內模 (ME-302 Inner Body)	1
白色(White)	301單件式內模 (301 Inner Body)	1										




Earth Ground (Green)
Ø4.75±0.15



Insulation Thickness 0.76 mm
Overall Diameter 2.7±0.10 mm

Copper Conductor
41/0.160±0.004 mm
Resistance 22.4
(20°C Max). ohms/km)

Jacket Thickness 0.76 mm
Overall Diameter 7.8±0.15 mm



3048^{+50.8}_{-12.7}

包裝方式(Packing)

扎線方式 (Bulk Pack)	每 10 條一扎 Per 10 pcs/Ties
紙箱尺寸 (Carton Size)	480 X 320 X 250
包裝數量 (Packing Qty)	PCS
標籤 (Label)	UL Detachable Label

正側事項 (Carton Print)	依客戶要求印刷 (See Purchase Order)	1. 高壓測試:1500V/1Sec <3mA (Hi-Pot Test:1500v/1Sec <3mA)
------------------------	---------------------------------	--

電線印字內容 Wire Printed	使用 充實 線材 凹印字 (In-Filler, Gravure)	紙箱事項標記 Shipping Mark
E322763 (UL) SJT 18AWG(0.824mm ²)x3C VW-1 105°C 300V /JT c(UL) SJT 18AWG(0.824mm ²)x3C FT2 105°C 300V -LF-		CnC
(UL) SJT 18AWG(0.824mm ²)x3C VW-1 105°C 300V E77975 WONDERFUL-D CSA SJT 18AWG(0.824mm ²)x3C FT2 105°C 300V LL43774 -F- -LF-		

SIGNATURE	NAME	DATE			
APPROVED					
M.F.G. CHECKED			00	2011 1121	新版發行 楊承正
Q.A. CHECKED			REV	DATE	DESCRIPTION SYMBOL
DRAWN	楊承正	2011.11.21	PART No.	800-18-13D-WH-0010F	
CUSTOMER			DWG No.		

SIZE:	A4
UNIT:	mm
SCALE:	1:1
PROJ.	

CnC Tech, LLC

Industrial Cable and Connector Technology