



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us



Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




插頭部件 (Plug Component)			頭部剥皮尺寸 (Dimensions)			線材規格 (Wire Styles)	尾部剥皮尺寸 (Dimensions)			尾插部件 (Connector Component)		
顏色(Color)	零件描述(Component)	Qty.	內剥(Strip)	外剥(ROJ)	顏色(Color)		外剥(R.O.J)	內剥(Strip)	顏色(Color)	規格描述(Instruction)	Qty.	顏色(Color)
35P 黑色 (Black)	ME-101A (1-15P, Non-Polarized)	1	6 <sup>+1</sup> <sub>-0</sub>	15 ± 2	黑/Black(L)	SPT-2 18AWG*2C 105°C 黑色 (BLACK) Length : 2000±50 (79"±2")	15 ± 2	5 <sup>+1</sup> <sub>-0</sub>	黑/Black(L)	FM-1FP (IEC 60320, C7, Polarized, 10A 125V~)	1	35P 黑色 (Black)
鍍鎳 (Nickel-Plated)	(8.0/6.3) 極性端子97662-1 (Polarized Solid Blades)	2	6 <sup>+1</sup> <sub>-0</sub>	15 ± 2	白/White(N)		15 ± 2	5 <sup>+1</sup> <sub>-0</sub>	白/White(N)	O-Type Receptacle Terminal	2	銅本色 (Brass-Natural)




ME-101A (NEMA 1-15P)  
(Dimensions of Plug Face)



SPT-2 18AWGx2C 截面圖  
(Wire Cross-Section)



B-C2 扎線圖示 (Tied Loop Hank Detail)



FM-1FP (IEC 320, C7, Polarized)  
(Dimensions of Connector Face)

REV	DATE	REVISE CONTENT
A	08/30-2012	The first edition is issued and drawing.
F		

- NOTE:**
- Hi-Pot Test : 1500V/1Sec ; <0.5mA.
  - Insulation Resistance Test : DC 500/min >100 meg-ohm.
  - Continuity & Polarization Test : No short circuit, break circuit, displacement.
  - Each end terminal shall be capable of withstanding a pull of 25lbs for 1 minutes without loosening.
  - Strain relief shall be capable of withstanding a pull of 35lbs for 1 minutes without loosening.
  - All material according to Non-toxic standard.(Material must be RoHS compliant.)
  - "FMC" logo maybe present on 1-15P.

線材印字 (Wire Printed)	充實, 油墨印字 (Un-Fillers, Printing Ink)	<b>CnC Tech, LLC</b> Industrial Cable and Connector Technology			
包裝方式 (Packing)					
Tied Hank	See Hank Detail	Chu8.		CnC	
Carton Size	480 x 320 x 180	DATE	P/N No. 800-1804-2-SPT2-BL-00200		
Pack Number	100 pcs/ <sup>UL Laster Labels</sup>	08/30-2012	MATERIAL		
Carton Print	See Purchase Order		PVC	UNIT	mm
TYPE	NEMA 1-15P Polarized to IEC 60320, C7 Power Supply Cord		Customer Approval		
DRAWING NO.	098MM1016	REV	A		

業務校閱 :  
品質校閱 :