



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DK-SERIES DKR 32 24VUC 1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



At just 6 mm wide, all components of the DKR minicouplers have an extremely narrow design. Weidmüller also offers 4 and 5 screw-connections, with a rated cross-section of 4 mm².

The mini-coupler is suitable for a wide range of applications. It is used for the coupling of digital sensor/actuator signals with automation devices on the process level..

General ordering data

Order No.	8008110000
Type	DKR 32 24VUC 1A
Version	DK-SERIES, Relays, No. of contacts: 1, NO contact, Rh/Ru, Rated control voltage: 24 V UC ±10 %, Continuous current: 0.5 A, Screw connection
GTIN (EAN)	4008190014100
Qty.	10 pc(s).

DK-SERIES
DKR 32 24VUC 1A

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Ratings**

Conductor connection system	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Open sides	right	Ambient temperature	-25 °C...+40 °C

Dimensions and weights

Width	6 mm	Height	75 mm
Depth	56 mm	Net weight	16.8 g

Temperatures

Operating temperature	-25 °C...+40 °C	Ambient temperature	-25 °C...+40 °C
Storage temperature	-40 °C...+60 °C		

Connection data

Clamping range, rated connection	4 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	4 mm ²		

Input

Rated control voltage	24 V UC ±10 %	Rated current AC	15 mA
Rated current DC	9 mA	Power rating	0.36 VA / 216 mW
Response / drop-out voltage AC coil	12 V / 8 V	Pull-in (sparkover) / drop-out voltage DC coil	10 V / 11 V
Pull-in / drop-out current, AC coil	6.3 mA / 4.3 mA	Pull-in / drop-out current, DC coil	3.8 mA // 3 mA
Status indicator	Green LED		

Output

Max. switching voltage, AC	100 V	Continuous current	0.5 A
making current	500 mA	Max. switching power	10 W / 10 VA
Switch-on delay	typically 0.7...2.5 ms	Switch-off delay	typical. 0.2...2.0 ms
Response time	typ. 0.7...2.5 ms / 0.2...2 ms	Min. switching power	1 V / 1 mA
Max. switching frequency at rated load	5 Hz		

Contact specifications

No. of contacts	1	Contact design	NO contact
Contact material	Rh/Ru	Mechanical service life	10 ⁹ switching cycles

Insulation coordination

Rated voltage	150 V	Clearance and creepage distances for control side - load side	≥ 3 mm
Dielectric strength to mounting rail	4 kV _{eff}	Impulse withstand voltage	1.5 kV
Protection degree	IP 20	Pollution severity	2
Surge voltage category	III		

Other technical data

Version	Relay coupler	Status indicator	Green LED
Free-wheel diode	No	Reverse polarity protection	not available

**DK-SERIES
DKR 32 24VUC 1A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Further details of approvals / standards**

Standards DIN EN 50178

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	40-02-06-14
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

Approvals

Approvals

**Downloads**

Declaration of Conformity [K069_02_11.pdf](#)

**DK-SERIES
DKR 32 24VUC 1A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Electric symbol**