



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





ESD High Temp Masking Tape

Used in applications masking PCB gold features for wave soldering

- Waterproof
- Does tribocharge, but has minimal charge retention
- 7 mil (0.007" or 0.18 mm) total thickness
- Adhesive surface 1.2×10^{11} ohms
- Film resistance $< 1 \times 10^{11}$ ohms tested per ANSI/ESD S11.11 at 50% RH
- Max Temp 135°C (275°F) 45 minutes max
- Non-toxic
- pH neutral
- Non-corrosive
- Tensile: 22 lbs./in.
- Adhesion to Steel: 35 oz./inch²
- Elongation: 8%
- Temperature Range: -32°F to +275°F
- Adhesive Mass: Natural Rubber
- Adhesive: Non-Staining
- Excellent Conformability



Tape is wound on a paper core.

The user must determine the suitability for use of the product for its intended use

Users shall determine the suitability of the product for its intended use. For best results, tape inventory should be continually replenished. It is recommended that rolls of tape be stored flat and rotated (flipped over to the other side) periodically. Tapes should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Tape should not be stored in ultraviolet sunlight, moisture, or heat. Tape over one year old should be evaluated by the user to determine acceptability for the user's application. Desco Industries, Inc. recommends those tracking useful life of product to use shipping/invoice date as Desco Industries, Inc. expressly warrants that for a period of one (1) year from the date of purchase, our Wescorp Brand ESD Tape will be free of defects in material (parts) and workmanship (labor). See details of Limited Warranty online at Desco.com/Warranty.aspx

Specifications and procedures subject to change without notice.

Note: Waterproof release coating does generate static charges during unrolling. We recommend slow unwinding, utilizing an Ionizer to neutralize charge.

Width - See Table Below

Tape	0.5"	.75"	1"	Core	Length
ESD High Temp Masking	81260	81261	81262	3"	60 yds

Width tolerance $\pm 1/32$ "

Tape widths are nominal metric ± 0.8 mm ($\pm 1/32$ ").

1/2" is 12 mm nominal or 0.472"

3/4" is 18 mm nominal or 0.709"

1" is 24 mm nominal or 0.945"

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at Desco.com.

*Wescorp is a Desco Industries brand.

WESCORP* ESD HIGH TEMP MASKING TAPE, PAPER CORE

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING
NUMBER
81260

DATE:
November
2009

DESCO