imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Sheet Metal Tools/HVAC

Klein's line of HVAC tools make it easy to work with sheet metal, ductwork and tubing. These job-matched tools are proven to stand the test of time with superior results.

For Professionals... Since 1857™



Sheet Metal Tools/HVAC



Additional Features:

- J1100L, J1101R, J1102S Journeyman snips cut 18 gauge cold rolled steel and 22 gauge stainless steel
- J2103S Journeyman Bulldog snips cut 16 gauge cold rolled steel and 18 gauge stainless steel

J1102S

J1101R


Cat. No.	Cutting Pattern	Snip Type	Cutting Length	Color Code	Cutting Capacity: Cold Rolled/Stainless Steel	Overall Length	Weight
J1100L	Left/Straight	Aviation	1-3/8" (34.9 mm)	Red/Black	18 Gauge/22 Gauge	9-7/8" (250.8 mm)	14.4 oz. (408 g)
J1101R	Right/Straight	Aviation	1-3/8" (34.9 mm)	Green/Black	18 Gauge/22 Gauge	9-7/8" (250.8 mm)	14.7 oz. (417 g)
J1102S	Straight/Wide Curves	Aviation	1-1/2" (38.1 mm)	Yellow/Black	18 Gauge/22 Gauge	10-1/16" (255.6 mm)	14.4 oz. (408 g)
J2103S	Notch/Straight	Bulldog	7/8" (22.2 mm)	Yellow/Black	16 Gauge/18 Gauge	9-7/16" (239.7 mm)	13.9 oz. (394 g)

Right Angle Snips

Additional Features:

- J2104L, J2105R Journeyman snips cut straight, curves, and tight circles in 24 gauge cold rolled steel and 28 gauge stainless steel
- Makes cutting easier in confined spaces (in ductwork, reaching through openings or against a wall)

Cat. No.	Cutting Pattern	Snip Type	Cutting Length	Color Code	Cutting Capacity: Cold Rolled/Stainless Steel	Overall Length	Weight
J2104L	Left Curves/Tight Circles/Straight	Right Angle	1-1/4" (31.8 mm)	Red/ Black	24 Gauge/28 Gauge	7-15/16" (201.6 mm)	14.4 oz. (408 g)
J2105R	Right Curves/Tight Circles/Straight	Right Angle	1-1/4" (31.8 mm)	Green/ Black	24 Gauge/28 Gauge	7-15/16" (201.6 mm)	14.4 oz. (408 g)





J2104L

J2105R

J1100L



Sheet Metal Tools/HVAC

JOURNEYMAN

Cutting & Notching Tools

Offset Snips

Additional Features:

J2101R

- J2100L, J2101R, J2102S and J2106S snips feature exclusive Klein Kurve[™] handles for natural hand positioning and ease of use
- J2106S Journeyman snips cut 20 gauge cold rolled steel and 24 gauge stainless steel, with a 2-3/8" length of cut for faster cutting
- J2100L, J2101R, J2102S Journeyman snips cut 18 gauge cold rolled steel and 22 gauge stainless steel



Cat. No.	Cutting Pattern	Snip Type	Cutting Length	Color Code	Overall Length	Cutting Capacity: Cold Rolled/Stainless Steel	Weight
J2100L	Left/Straight	Offset	1-1/4" (31.8 mm)	Red/Black	9-1/2" (241.3 mm)	18 Gauge/22 Gauge	15.5 oz. (439 g)
J2101R	Right/Straight	Offset	1-1/4" (31.8 mm)	Green/Black	9-1/2" (241.3 mm)	18 Gauge/22 Gauge	15.7 oz. (445 g)
J2102S	Straight/Wide Curves	Offset	1-1/2" (38.1 mm)	Yellow/Black	9-1/2" (241.3 mm)	18 Gauge/22 Gauge	15.5 oz. (439 g)
J2106S	Straight/Wide Curves	Long Cut Offset	2-3/8" (60.3 mm)	Yellow/Black	10-1/2" (266.7 mm)	20 Gauge/24 Gauge	1.1 lbs. (0.50 kg)

Cutting & Notching Tools

Aviation Snips - Regular/Offset/Bulldog

- Forged and heat-treated steel blades for strength and durability
- Regular and offset blades have the capacity of cutting 18 gauge cold-rolled sheet metal and 22 gauge stainless steel sheet metal
- Offset blades provide ease of cutting tight curves and keep user's hand away from metal
- Bulldog snips (Cat. No. 2103) for notching or trimming 16 gauge cold-rolled sheet metal and 18 gauge stainless steel sheet metal
- Spring-loaded for self-opening action
- Latch keeps jaws closed when not in use
- Hardened handles for extra strength
- Contoured plastic handles are comfortable and color-coded by cutting pattern

Cat. No.	Cutting Pattern	Snip Type	Cutting Length	Color Code	Overall Length	Cutting Capacity	Weight
1100L	Left/ Straight	Aviation	1-3/8" (34.9 mm)	Red	9-3/4" (247.7 mm)	18 Gauge	14.4 oz. (408 g)
1101R	Right/ Straight	Aviation	1-3/8" (34.9 mm)	Green	9-3/4" (247.7 mm)	18 Gauge	14.7 oz. (417 g)
1102S	Straight/ Wide Curves	Aviation	1-1/2" (38.1 mm)	Yellow	10-1/8" (257.2 mm)	18 Gauge	14.4 oz. (408 g)
2100L	Left/ Straight	Offset	1-1/4" (31.8 mm)	Red	9-1/2" (241.3 mm)	18 Gauge	15.5 oz. (439 g)
2101R	Right/ Straight	Offset	1-1/4" (31.8 mm)	Green	9-1/2" (241.3 mm)	18 Gauge	15.7 oz. (445 g)
2102S	Straight/ Wide Curves	Offset	1-1/2" (38.1 mm)	Yellow	9-1/2" (241.3 mm)	18 Gauge	15.5 oz. (439 g)
2103	Notch	Bulldog	7/8" (22.2 mm)	Yellow	9-1/4" (235 mm)	16 Gauge	13.9 oz. (394 g)







Replacement springs for aviation snips				
Cat. No.	Description			
P-406	Replacement Spring, Cat. No. 1100L, 1102S			
P-407	Replacement Spring, Cat. No. 1101R			

230

See page 310 for additional information on warnings.





Hand Notcher	
 Allows quick, clean, 30° "V" shaped cuts in sheet metal 	
 Drop-forged, high-impact steel jaw with 13/16" (21 mm) maximum throat depth 	
 Jaws' hook design allows easy notching of corners and take-off tabs without slippage 	
 All steel construction with nickel-plate and black-oxide finish provides long life and durability 	86551
 Hardened steel handles include hand guards and are covered with vinyl grips for added comfort and easy operation 	

).	Overall Length	Handle Color	Weight	Cat. No.	Overall Length	Handle Color	Weight
	8" (203.2 mm)	Blue	1.0 lbs. (0.45 kg)	86551	8-1/2" (215.9 mm)	Blue	1.0 lbs. (0.45 kg)

Lightweight Tinner Snips

Cat. No.

86560

- 6° angled, hollow-ground cutting edge for cutting full 3-1/2" (89 mm) straight cuts and wide curves
- Easily replaceable cutting blades made of high-carbon steel
- Cutting capacity: 22 gauge cold-rolled sheet metal; 26 gauge stainless steel sheet metal. Do not use to cut hardened wire, nails, or any other rounded surface
- Lightweight magnesium handles

000.0				
330.2 mm)	Gray	13.4 oz. (380 g)		
Description				
Replacement Blades for Tinner Snips				
	Description	Description		

Seaming & Folding Tools

Seamers - Straight and Offset

- Compound-leverage mechanism easily and accurately bends, seams, and flattens sheet metal and non-ferrous metals
- Jaw marked in 1/4" (6 mm) increments for precise bending measurements
- All-steel construction and nickel-chrome plated hardware provide long life and durability
- Vinyl grips with handle stops for added comfort and easy operation
- Straight-handle model is used for most general applications
- Offset-handle model (not pictured) is for use in overhead or confined areas
- Broader jaw model for forming wider folds
- Folds 22 gauge CRSM and 24 gauge SSSM



Cat. No.	Туре	Jaw Size	Overall Length	Handle Color	Weight
86553	Straight-Hand Seamer	3" (76.2 mm)	8-3/8" (212.7 mm)	Blue	1.5 lbs. (0.68 kg)
86552	Offset-Hand Seamer	3" (76.2 mm)	8" (203.2 mm)	Blue	1.5 lbs. (0.68 kg)

See page 310 for additional information on warnings.



3100



Sheet Metal Tools/HVAC

Seaming & Folding Tools

Folding Tools

- Two folding depths: 3/8" (10 mm) and 1" (25 mm)
- Handy sight gauges for accurate depth alignment
- Made of heavy-duty 16 gauge steel for folding strength



Cat. No.	Overall Length	Folds	Weight
88981	18" (457.2 mm)	24 Gauge CRSM and 28 Gauge SSSM	2.0 lbs. (0.91 kg)

Tube Benders & Cutters

Professional 4-in-1 Tube Bender

- Bends four popular tube sizes
- Calibrated markings for accurate left-hand, right-hand, and offset bends up to 90°
- For soft copper, aluminum, and steel tubing
- Bends 3/16", 1/4", 5/16" and 3/8" (6 mm and 8 mm) O.D. tubing

Cat. No.	Closed Overall Length	Weight
89030	10" (254 mm)	1.0 lbs. (0.45 kg)



Professional Tube Cutter

- Accurate 4 roller tracking system no spiraling
- Professional reaming tool for stainless steel tubing
- Extra cutting wheel included in handle

Cat. No.	Overall Length	Cuts	Weight
88904	6-1/32" (153.2 mm)	1/8" to 1-3/8" (3.2 to 34.9 mm) Steel and Copper Tubing	1.3 lbs. (0.59 kg)
Cat. No.	Description		Weight
88905	Replace	1.3 oz. (37 g)	



88904

88981

Professional Mini Tube Cutter

- Perfect for tight space cutting. Requires only 1-3/8" (34.9 mm) swing radius
- Smooth feed mechanism for precise, right angle cutting action
- For copper and aluminum tubing; not designed for cutting stainless steel or hard tempered tubing

Cat. No.	Cuts	Overall Length	Weight
88977	1/8" to 5/8" (3.2 to 15.9 mm) O.D. Tubing	1-3/4" (44.5 mm)	2.5 oz. (71 g)
Cat. No.	Description		Weight
88978	Wheels and Screw for Mini Tube Cutter		2.5 oz. (71 g)





88978

88977

See page 310 for additional information on warnings.



www.kleintools.com



66400

89565

Swaging Tool – Punch Type

Professional 6-in-1 Swaging Punch

- Swages six sizes of tubing
- Hex design for ease of extraction
- Precision machined surface for ease of forming
- High-alloy steel, heat-treated for strength and durability



 Cat. No.
 Swages
 Overall Length
 Weight

 66400
 3/16" (4.8 mm), 1/4" (6.4 mm), 5/16" (7.9 mm), 3/8" (9.5 mm), 5-13/16" (147.6 mm)
 5.9 oz. (167 g)

 1/2" (12.7 mm), 5/8" (15.9 mm) O.D. Tubing
 5-13/16" (147.6 mm)
 5.9 oz. (167 g)

Duct Stretcher

Duct Stretcher

- Aligns and pulls ductwork together, easing installation of drive cleats
- Offset handle protects hand

Cat. No.	Overall Length	Weight
89565	16" (406.4 mm)	12.0 oz. (340 g)

Crimping Tools

5-Blade Crimper

Crimps

Cat. No.

- Produces factory-precision indentations in stove pipe and round duct with just a squeeze
- Compound-leverage mechanism, heavy-duty jaw/handle linkage, and closing stop provide
- easy operation and consistent crimps for virtually leak-proof connections
 Hardened steel handles include hand guards covered with vinyl grips for added comfort and easy operation
- All steel construction and nickel-plating provide long life and consistent crimp profile



86550 24 Gauge CRSM and 28 Gauge SSSM 9" (228.6 mm) Blue 1.0 lbs Refrigeration Wrenches

Ratcheting Refrigeration Wrenches

• Fully reversible for refrigeration-packing gland nuts, valve stem sockets and beam-clamp installation

Overall Length

Handle Color

- Compact in size, with clearly marked sockets for four nut sizes
- Quick-flip reversing lever permits instant ratchet reversal
- · Ruggedly built with polished chrome finish for smooth edges for comfort

Cat. No.	Socket Size	Overall Length	Weight
68309	3/16" and 1/4" Sq. x 1/2" and 9/16" Hex	6-13/16" (173.0 mm)	6.9 oz. (196 g)
68310	3/16" and 5/16" Sq. x 1/4" and 3/8" Sq.	5-1/2" (139.7 mm)	3.2 oz. (91 g)



68310

See page 310 for additional information on warnings.





Magnetic Hex Drivers

Magnetic Hex Drivers

- For driving sheet metal screws
- Strong Rare Earth magnets for maximum holding
- 1/4" (6.4 mm) hex shank with quick release groove



86602

Cat. No.	Description	Overall Length	Weight
3-Pack			
86600	1/4" Magnetic Hex Drivers Pk 3	1-3/4" (44.5 mm)	1.9 lbs. (0.86 kg)
86601	5/16" Magnetic Hex Drivers 3 pack	1-3/4" (44.5 mm)	2.2 oz. (62 g)
86602	3/8" Magnetic Hex Drivers 3 pack	1-3/4" (44.5 mm)	2.6 oz. (74 g)
10-Pack Punch Card	for Individual Sale		
8660010	1/4" Magnetic Hex Drivers Pk 10	1-3/4" (44.5 mm)	6.9 oz. (196 g)
8660110	5/16" Magnetic Hex Drivers 10 pack	1-3/4" (44.5 mm)	7.8 oz. (221 g)
8660210	3/8" Magnetic Hex Drivers 10 pack	1-3/4" (44.5 mm)	9.1 oz. (258 g)

Nylon Tie Tensioning Tools

Nylon Tie Tensioning Tools

- Designed for work with ties rated at 120 250 lbs. (54 113 kg)
- Tensions up to 65 lbs. of force (30 kg)
- Maximum tie width of 15/32" (12 mm)
- Handle grips for comfort
- Excess tie material is automatically cut off (Cat. No. 86571 only)

Cat. No.	Description	Weight
86570	Nylon Tie Tensioning Tool	13.9 oz. (395 g)
86571	Nylon Tie Tensioning Tool Auto Cutoff	1.0 lbs. (0.45 kg)



Special-Purpose Knife

Special-Purpose Knife

- Cuts duct board and flexible duct
- Double-edged knife: regular and serrated
- Cushion-grip handle for comfort
- Includes puncture resistant nylon sheath with belt loop

Blade Material

Stainless Steel



DK06

B	lade Length	Weight	No.
5-	1/2" (139.7 mm)	8.5 oz. (241 g)	



www.kleintools.com

Cat. No.

DK06



15-in-1 Screwdriver/Nut Drivers

- Multi-bit driver includes 14 different screwdriver tips plus a 1/4" (6.4 mm) nut driver
- Internal storage for screwdriver bits



Cat. No.	Description	Shank Length	Slotted Bits	Phillips Bits	Square Bits	Nut Driver Sizes	TORX Bits	Other Bits	Overall Length	Weight
32292 NEW!	HVAC Multi-Bit Screwdriver 15 Pc	4" (101.6 mm)	4 mm, 6 mm	#0, #1, #2, #3	#1, #2	1/4"	#10, #15, #20, #25	Schrader [®] Valve Insertion, Core Removal	8-1/2" (215.9 mm)	8.0 oz. (227 g)

Schrader[®] is a registered trademark of Schrader-Bridgeport International, Inc.


11-in-1 Screwdriver/Nut Driver with Schrader[®] Valve Removal/Installation Bit

- Great for HVAC and other industrial applications
- Includes unique style bit for installation/removal of common TR-4 Schrader[®] valves and aggressive thread extractor tip for backing out broken cores

		0						
Cat. No.	Shank Length	Slotted Bits	Phillips Bits	Square Bits	Nut Driver Sizes	Other Bits	Overall Length	Weight
32527	4" (101.6 mm)	1/4" (6.4 mm) and 3/16" (4.8 mm)	#1 and #2	#1 and #2	3/8", 5/16" and 1/4"	Schrader [®] Valve Core Removal/ Installation - Extractor	7-3/4" (196.9 mm)	7.0 oz. (198 g)

Schrader[®] is a registered trademark of Schrader-Bridgeport International, Inc.

2-in-1 Hex Head Screwdriver



- Powerful magnets for maximum fastener retention
- Solid build quality; feels like a conventional nut driver
- Color coded bands for easy identification
- Wrench-assist to help remove stubborn fasteners



Cat. No.	Тір Туре	Tip Size	Shank Length	Overall Length	Weight
65064 NEW!	Hex	1/4" x 5/16" (6.4 x 7.9 mm)	3-5/8" (92.1 mm)	8" (203.2 mm)	7.2 oz. (204 g)

10-in-1 Folding Screwdriver/Nut Driver

- Conveniently folds up for easy storage or to fit into your pocket
- Each driver arm contains four interchangeable bit styles and two nut drivers
- Unfold each driver arm up to a full 180° for straight on driving power, or at 90° for extra leverage on stubborn fasteners
- The quick release button easily unlocks a fully extended driver arm



Cat. No. Handle Color **Slotted Bits Phillips Bits Square Bits Nut Driver Sizes Other Bits** Weight 32534 Blue 1/4" (6.4 mm) and #1 and #2 #1 and #2 5/16" and 1/4' Valve Core Removal/ 5.9 oz. (167 g) 3/16" (4.8 mm) Installation - Extractor Schrader® is a registered trademark of Schrader-Bridgeport International, Inc. TORX® is a registered trademark of Acument Intellectual Properties, LLC.

See page 310 for additional information on warnings.



32290

32527



Hammers

Setting Hammer

- Durable epoxy resin handle helps to protect neck from fraying and splintering if incorrectly struck or over struck
- High-strength fiberglass shaft absorbs shock and keeps head tight
- Cushioned, PVC grip bonded to handle
- Special high-carbon steel, octagon shaped head with flat striking surface and rounded cross peen



Cat. No.	Head Weight	Overall Length	Weight
820-16	16.0 oz. (454 g)	13" (330.2 mm)	1.6 lbs. (0.73 kg)

Riveting Hammer

- High-carbon steel round head is forged and hardened
- Flat striking surface with rounded cross peen
- Straight-grain American hickory handle is stained and lacquered



Cat. No.	Head Weight	Overall Length	Weight
821-12	12.0 oz. (340 g)	12-1/4" (311.2 mm)	1.1 lbs. (0.50 kg)

Dead Blow Hammers

- Durable, abrasion resistant non-marring hammer face
- Increased striking force with zero impact rebound
- Design isolates user from striking impact and reduces fatigue
- 40% more driving power than othe rdead blow hammers
- Protects job surface from damage
- Applications: HVAC, metal fabrication, electronics, oil and mining, wood and metal assembly, automotive, aerospace

Cat. No.	Head Weight	Overall Length	Weight
811-16	16.0 oz. (454 g)	12-1/2" (317.5 mm)	1.4 lbs. (0.64 kg)
811-32	32.0 oz. (907 g)	18" (457.2 mm)	1.8 lbs. (0.82 kg)



