# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





#### 0.5 Nm RPT5 1.4 and 3.2 Watts 1.4 W Part number 82712004



- Gearbox 0.5 Nm
- Motor power max. 3.2 W
  Class A EMC interference suppression (radiated)
- Compatible with 6 V, 9 V or 12 V battery power supply
- Optional class B interference suppression
- Optional 1, 5, 12 or 48 pulses/rev encoder

#### Part numbers

Туре	Туре	Voltage	Output speed (rpm)	Ratios (i)
82712004 1.4 W	827120	12 V	109	30,5

#### Specifications


General characteristics	
Motor	82710001
Gearbox	810220
Maximum permitted torque from gearmotor under continuous conditions (for 0.5 million turns) (Nm)	0,5
Axial load static (daN)	1
Radial load static (daN)	4
Max. output power (W)	1,4
Nominal output (W)	1
Gearbox case temperature rise (°C)	40
Weight (g)	80

#### Made to order products, available on request

For more than 1000 pieces

- 48 pulses/rev encoder
  Class B filter
- Case N°2 (for other fixing points see diagram) ; check whether mounting is possible
- Gearbox shaft
- Connections
- For other types please consult Crouzet

### Dimensions (mm)



Nº	Legend
1	3 fixing holes M3
0	2 solder tags 2.8 x 0.5 mm
8	(Pushed-in shaft)

Curve : torque/nominal speed 827120

Curves

### 

•	Special supply voltage
2	Lead output
•	Special connectors
	Special shaft
	Special reduction ratio
	<ul> <li>Special materials for gears</li> </ul>
	Special adaptor plate
	Class B EMC filter
	Greasing at low temperature
	<ul> <li>1 to 48 pulses/revolution encoder</li> </ul>