



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**Part Number: 83006**

Hook-Up/Lead Wire UL AWM Style 1213, (1) 22 AWG (19x34) SPC, TFE, 105°C

[Request Sample](#)

## Product Description

One 22 AWG stranded (19x34) silver plated copper conductor, TFE insulation.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
22	19x34	SCC - Silver-coated Copper	1

Conductor Count:	1
Conductor Size:	22 AWG

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	0.048 in	0.009 in

#### Outer Jacket Material

Material	Nominal Diameter
No Jacket	0.05 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
15.75 Ohm/1000ft

Shielding:	Unshielded
------------	------------

#### Current

Element	Max. Recommended Current [A]
Mil-Std-975M Table 3.16 (single wire)	Mil-Std-975M Table 3.16 (single wire): 4.5 amps

#### Voltage

Description	Voltage Rating [V]
Mil-W-16878/4	600 V RMS Mil-W-16878/4

### Temperature Range

UL Temp Rating:	105°C
Operating Temp Range:	-70°C To +200°C

### Mechanical Characteristics

Bulk Cable Weight:	4 lbs/1000ft
--------------------	--------------

### Standards

UL AWM Style:	1213
Military Specification:	NEMA HP3, MIL-W-16878/4 (Except For Stranding)

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Footnote
83006 010100	Black	E
83006 0101000	Black	
83006 010500	Black	E S
83006 006100	Blue, Light	E
83006 0061000	Blue, Light	E S
83006 006500	Blue, Light	E S
83006 001100	Brown	E
83006 0011000	Brown	E S
83006 001500	Brown	E S
83006 008100	Gray	E
83006 0081000	Gray	E S
83006 005100	Green, Dark	E
83006 0051000	Green, Dark	E S
83006 005500	Green, Dark	E S
83006 003100	Orange	E
83006 0031000	Orange	E S
83006 002100	Red	E
83006 0021000	Red	
83006 002500	Red	E S
83006 0071000	Violet	E S
83006 007100	Violet	E
83006 009100	White	E
83006 0091000	White	
83006 009500	White	E S
83006 004100	Yellow	E
83006 0041000	Yellow	E S
83006 004500	Yellow	E S

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
Footnote:	S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE)

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

